


ESD table mat Premium, light blue, 600 x 1200 x 2 mm, cut to size with 2x 10 mm push button



With the SafeGuard ESD table mat set XS Pro, you get a high-quality product that has been specially developed for electronics production. The set consists of a two-layer ESD table mat with dimensions of 600 x 400 mm and a thickness of 2 mm, which is not only resistant to heat and solder, but also to chemicals and oil. Thanks to its permanent elasticity, the mat no longer rolls up and therefore always remains flat. The abrasion-resistant surface ensures a long service life and offers you maximum comfort at work.

All components are easily connected to each other and provide reliable ESD protection. The SafeGuard ESD table mat set XS Pro is RoHS-compliant and meets all the requirements for effective ESD protection in electronics production.

In addition, we now offer you the option of customizing your work clothing. Whether with your company logo or another motif, we will implement your wishes and make your jacket unique. You can find more information at <https://www.weidinger.eu/de/individuelle->

bedruckung

- Heat and solder resistant
- Temperature resistant according to Glow wire test - IEC 60335-1:2010 - up to 750°C and Needle Flame test acc. to IEC 60695-11, up to 30sec.
- Resistant to chemicals and oil
- Permanently elastic, abrasion-resistant and comfortable
- RoHS compliant
- Anti-reflective surface makes working easier
- Two-layer ESD table mat (dissipative/conductive)
- Surface resistance is $10^6 - 10^7$ Ohm (EN 61340-2-3)

item number	WL34499
model	SG-TM-HB-GL-2DK-1200X600X2
manufacturer	SAFEGUARD
manufacturer item number	SG-TM-HB-GL-2DK-1200X600X2
GPSR manufacturer information	Weidinger GmbH Hertha-Sponer-Str. 1a DE-82216 Gernlinden
length	1200 mm
width	600 mm
height	2 mm
order unit	1 piece
content unit	1 piece
colour	light blue
colour manufacturer	light blue
Colour	blue
material	Natural rubber & synthetic rubber
RoHS conform	yes
Typical surface resistance (Rpp)	$10^6 - 10^7$ Ohm (EN 61340-2-3)
connection	2x 10 mm press stud
type of lining	table mat
ESD certification acc. to IEC 61340-5-1:2016	yes
Temperature resistance	Glow wire test acc. to IEC 60335-1:2010 - up to 750°C
Volume Resistance RV EN 61340-2-3	10^6 Ohm
Hardness ISO 7619	shore A 75
Material resistance/pressure EN/ISO 24343-1	< 0,20mm

Abrasion resistance ISO 4649 (Met. A-5N)	< 200mm ³
Flexibility EN/ISO 24344 (Met.A O 20mm)	yes
Flammability	Needle Flame test acc. to IEC 60695-11, bis 30sec.
Slip resistance, dynamic COF EN13893	> 0,30
Resistance against stains EN/ISO 26987	Resistant, depending on concentration and duration of contact
Resistance to oils and greases ASTM D471	Limited change in volume and mass
surface	Two-layer ESD table covering
corners	rounded
ESD safe	yes

Other versions

item number	length x width
WL54960	400 mm x 400 mm
WL43389	400 mm x 600 mm
WL43390	600 mm x 600 mm
WL43391	700 mm x 1200 mm
WL43392	800 mm x 1200 mm
WL34495	900 mm x 600 mm
WL34499	1200 mm x 600 mm