

## WXR 3030, 3-channel rework station 420 W (600 W)



Everything - and more.

The WXR3 Rework station is the perfect solution for all soldering, desoldering and hot-air jobs. The WXR3 can handle the most demanding tasks but is also ideal for standard jobs. All units can cope with major manufacturing tasks quickly and surely thanks to their straight-forward settings. The station can also be integrated into a traceability process.

600 Watts – unique

The WXR 3 is a 3-channel station with a total output of 600 W. The multifunctional WXR 3 is suitable for all applications, and can work with all WX tools.

Two integrated pumps (self-contained)

A pair of integrated pumps make the system independent of a separate compressed air supply. A high-performance pump for vacuum and hot air, and a separate vacuum pump for pick-up tools.

Automatic / intelligent power management

The rework station provides 600 watts of power. Its intelligent power management function allows the available power to be distributed to the connected tools as required – a total of 600 watts. High-performance tools can be operated at the same time. 3

Products for the electronic industry



channels, 200 watts each.

User-friendly and easy to navigate

The LCD display shows all connected tools. Special functions can easily be set at the press of a button.

- Max. Hot air quantity l/min (depending on tool): 15
- Flow rate l/min: 18
- Built-in pump: intermittent operation 30/30 s
- Display: 240 x 88 dots / backlight
- Overcurrent release: 2.0 A
- USB interface for firmware update, parameterization and monitoring; any commercially available USB memory stick fits into the USB interface
- IPC compliant
- WX compatible

item number	WL34966
model	WXR 3030
model line	WXR 3
manufacturer	WELLER
manufacturer item number	T0053501699N
length	273 mm
width	235 mm
height	102 mm
scope of supply	1x WXR 3 supply unit 1 set of WXHAP 200 hot air pistons, including safety rest 1 set of desoldering iron WXDP 120, including safety rest 1 set WXP 65 desoldering iron, including safety rest 1x WVP vacuum pipette 1x desoldering nozzle pliers PDN 1x mains plug 1x operating instructions
length in inches	10.75 in
width in inches	9.25 in
height in inches	4.02 in
order unit	1 piece
content unit	1 piece
power	420 W
voltage	230 V

Products for the electronic industry



vacuum	max. 0,7 bar
temperature range °C	100 – 450 °C
temperature range °F	200 – 850 °F
temperature accuracy °F	±17 °F
station type	soldering station
temperature stability °C	±2 °C
temperature stability °F	±4 °F
number of channels	3
ESD safe	yes