

## WXR 3032, 3-channel rework station, 420 W (600 W)



Everything - and more.

The WXR3 Rework station is the perfect solution for all soldering, desoldering and hot-air jobs. The WXR3 can handle the most demanding tasks but is also ideal for standard jobs. All units can cope with major manufacturing tasks quickly and surely thanks to their straight-forward settings. The station can also be integrated into a traceability process.

600 Watts – unique

The WXR 3 is a 3-channel station with a total output of 600 W. The multifunctional WXR 3 is suitable for all applications, and can work with all WX tools.

Two integrated pumps (self-contained)

A pair of integrated pumps make the system independent of a separate compressed air supply. A high-performance pump for vacuum and hot air, and a separate vacuum pump for pick-up tools.

Automatic / intelligent power management

The rework station provides 600 watts of power. Its intelligent power management function allows the available power to be distributed to the connected tools as required – a total of 600 watts. High-performance tools can be operated at the same time. 3 channels, 200 watts each.

User-friendly and easy to navigate

Products for the electronic industry



The LCD display shows all connected tools. Special functions can easily be set at the press of a button.

- Built-in pump: intermittent operation 30/30 s
- Display: 240 x 88 dots / backlight
- IPC compliant
- WX compatible
- USB interface for firmware update, parameterization and monitoring; any commercially available USB memory stick fits into the USB interface
- Overcurrent release: 2.0 A

<b>item number</b>	<b>WL35336</b>
model	T0053503699
model line	WXR 3
manufacturer	WELLER
manufacturer item number	T0053503699N
length	273 mm
width	235 mm
height	102 mm
scope of supply	WXHAP 200 Set: Hot air piston set with safety rest WXR 3: 3-channel supply unit, 420 W WXDV 120 Set: Desoldering iron set for vertical working, with safety rest WVP Vacuum pipette PDN Desoldering nozzle pliers for changing suction nozzles
length in inches	10.75 in
width in inches	9.25 in
height in inches	4.02 in
order unit	1 piece
content unit	1 piece
power	420 W
voltage	230 V
vacuum	max. 0,7 bar
temperature range °C	100 – 450 °C
temperature range °F	200 – 850 °F
temperature accuracy °F	±17 °F
station type	rework station
temperature stability °C	±2 °C

Products for the electronic industry



temperature stability °F	±4 °F
number of channels	3
air volume	18 l/min
ESD safe	yes