

ESD Precision Electronic Gripping Pliers, flat



Precision Electronics Gripping Pliers ESD The range for the highest demands on performance and results. Precision pliers for fine assembly work, e.g. in electronics and precision mechanics. For gripping, holding and bending. Handles electrically conductive dissipative. Bolted joint: precise, backlash-free movement of the pliers. Precisely machined joint surfaces for smooth, low-friction movement throughout the entire opening range. Low friction double spring for smooth and even opening. Precision laser-etched cross-locking. Non-glare finish. Light weight. Ergonomic, two-tone, multi-component ESD handles; black/grey. flat, wide jaws. precision laser-cut cross-scoring. - Shape: 4 - Jaw length (B): 21.9mm - Jaw thickness (at joint) (D): 6.5mm - Tip width (E): 1.4mm - Tip thickness (F): 3.5mm - Head width (A): 11.2mm - ESD: Yes

- The range for the highest demands on performance and results
- Precision pliers for fine assembly work, e.g. in electronics and precision mechanics
- For gripping, holding and bending
- Handles electrically conductive dissipative
- Bolted joint: precise, backlash-free operation of the pliers
- Precisely machined joint surfaces for smooth, low-friction movement over the entire opening range
- Low friction double spring for smooth and even opening
- Precision laser-cut cross-locking
- Non-glare finish
- Light weight
- Ergonomic, two-tone, multi-component ESD handle covers
- Black/grey

item number WL36013







Products for the electronic industry







model	34 42 130 ESD
manufacturer	KNIPEX
manufacturer item number	34 42 130 ESD
length	133 mm
width	51 mm
height	20 mm
length with packaging	189 mm
width with packaging	72 mm
height with packaging	48 mm
Packaging volume	0.579 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	DIN EN 61 340-5, DIN ISO 9655
RoHS conform	no
surface	burnished
VDE	no
ESD safe	yes
type of handle	with multi-component sleeves
type of pliers	electronic pliers









2/2