

2-channel supply unit for MFR-1300 series



The MFR-1300 Series desoldering and Rework Systems are standalone equipment. The power supply features an internal pump providing 0.7 bar pressure and 60 watts of SmartHeat®-Technology that makes through-hole desoldering easy and keeps your products safe from board damage. The new handpiece has been designed to be used in two configurations. As standard, the MFR-H5-DS desolder tool is a pencil grip design and a clip-on grip enables the handpiece to be used in a pistol style. The Solder collection chamber has a large capacity and the innovative replaceable tips enables reduced downtime and quicker changeover. Since the system has two switchable ports it can be used in addition with a soldering tip, cartridge or tweezers handpiece.

- Handstück Kabellänge: 183 cm (72"), brennbar, ESD-sicher
- Handstück-Stil: Standard/Kartusche
- Handstück - RF Stecker: 8-Pin rund DIN

item number

WL36440

Products for the electronic industry



model	MFR-PS1300
manufacturer	OKI
manufacturer item number	MFR-PS1300
order unit	1 piece
content unit	1 piece
product series	MFR series
typical bleeder resistance	$10^5 - 10^9 \text{ Ohm}$
power	110 W
voltage	240 V
suitable tips	SxP soldering cartridges, RxP rework cartridges, DxP desoldering cartridges
output power supply unit	60 W
station type	soldering station
ambient operating temperature	10 – 40 °C
length cable	1.83 m
ESD safe	yes