

WTHA 1, digital hot air station, 900 W



A compact, easy-to-use rework station. It is the first model on the market to feature a detailed LC display with self-explanatory user guidance for intuitive operation. The front-mounted power switch ensures easy operation. Unique LC display with detailed overview of all functions. Adjustable backlight. Power bar graph gives you visual control over soldering station to soldering iron power. The new menu button ensures maximum user-friendliness and easy navigation in the menu structure. The WT 1 / WT 1H can be stacked on top of the WTHA 1 to ensure more space at the workstation. Up to 5 pre-sets can be predefined, where air volume, temperature and time can be set individually. With the profile mode activated, it is possible to run all 5 settings in sequence.

- Modern operating concept, intuitive operation through clear menu navigation
- Low space requirement thanks to stackability
- 900 W hot air station for simple repair work and heating processes
- The temperature of the hot air is controlled electronically
- The brushless turbine ensures optimum hot-air setting
- Up to 5 programmable presets that can run automatically in one profile

Products for the electronic industry



- Housing cover can be used as an additional shelf
- Supply unit incl. shelf and permanently installed hot-air piston
- locking function
- Noise level (distance 1 m) dB(A): 56 dB(A) Distance 1 m at max. airflow
- built-in pump
- Display: Graphic LC display with backlighting
- WT compatible
- Flow rate l/min: 5-60 l / 20°C, 5-110 l / 300°C

Item no.	WL36828
Model	WTHA 1
Model line	WTHA 1
Manufacturer	WELLER
Manufacturer article no.	T0053173399
GPSR manufacturer data	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller-tools.com
Length	212 mm
Width	172 mm
Height	122 mm
Scope of delivery	1x hot air station WTHA 1 1x shelf 1x hot air piston 1x TNR 40 hot air round nozzle Ø 4 mm 1x mains plug 1x Operating instructions
Length in inches	8.35 in
Width in inches	6.77 in
Height in inches	4.8 in
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Power	900 W
Fuse	T 4A
Voltage	230 V
Air volume (max.)	50 l/min
Temperature range °C	50 – 600 °C
Temperature range °F	100 – 1000 °F

Temperature accuracy °F	± 54 °F
Included nozzle(s)	TNR 40
Station (type)	hot air station
Number of channels	1
ESD compliant	no

