

WT 1H, 1-channel supply unit, 150 W



This is how soldering is done today

When 90 watts are not enough, the high-power version with 150 watts is the right solution. The new powerful WT soldering stations set new standards in terms of user-friendliness. The detailed LC display provides a detailed overview of all functions - quickly and easily accessed via the new intuitive menu button. The lightning-fast exchange of the heating element during operation will in future enable work with several tips in quick change. If a tip has to be replaced, this is done independently of the heating element - which saves enormous costs. The innovative 2-in-1 tray with rotatable plunger holder ensures a free choice between wet and dry cleaning. All stations of the WT-Line fit perfectly on top of each other, thus saving considerable space at the workplace.

Front-mounted power switch

The front-mounted power switch ensures easy operation at all times.

Multifunctional LC display

Products for the electronic industry



Unique LC display with detailed overview of all functions. Adjustable backlight. Power bar graph allows you to visually check the current power of the soldering station.

Comfortable menu button

The new menu button ensures maximum user-friendliness and easy navigation in the menu structure.

Space-saving

The WT 1 / WT 1H can be stacked on top of the WTHA 1 to ensure more space at the workstation.

2-in-1 WSR tray

The piston holder can be rotated 180°. The user can choose between wet and dry cleaning.

- Housing cover can be used as an additional shelf
- Modern operating concept
- Intuitive operation through clear menu navigation
- Low space requirement thanks to stackability
- Graphic LC display with backlighting
- High functionality and flexibility - Numerous tools can be connected
- Automatic switch-off with integrated usage sensor in the tool
- locking function
- equipotential bonding
- WT compatible

item number	WL36829
model	WT 1H
model line	WT 1H
manufacturer	WELLER
manufacturer item number	T0053435699N
length	149 mm
width	138 mm
height	101 mm
length in inches	5.87 in
width in inches	5.43 in
height in inches	3.98 in
order unit	1 piece
content unit	1 piece
power	150 W

fuse	T2A
voltage	230 V
temperature range °C	50 – 550 °C
temperature range °F	150 – 999 °F
temperature accuracy °F	±17 °F
temperature stability °C	±2 °C
temperature stability °F	±4 °F
number of channels	1