

Cable shears with opening spring, Ø 15 mm / 50 mm², 165 mm



For cutting copper and aluminium cables, solid and stranded. Cuts smoothly and cleanly without crushing. Not suitable for steel wire and hard-drawn copper conductors. Hardened cutting edges with precision grinding. Easy cutting with one-hand operation. With clamping protection. Adjustable screw joint, self-locking. Opening spring located in the joint, protected and captive. - Shape: 2 - Cutting value Cu-cable, stranded: 50mm² - Cutting value Cu-cable, stranded: Ø 15mm - AWG: 1 / 0

- For cutting Cu and Al cables, solid and stranded
- Cuts smoothly and cleanly without crushing
- Not suitable for steel wire and hard drawn copper conductors
- Hardened cutting edges with precision grinding
- Easy cutting with one hand operation
- With clamping protection
- Adjustable screw joint, self-locking

Item no.	WL36892
Model	95 22 165
Manufacturer	KNIPEX
Manufacturer article no.	95 22 165
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	180 mm
Width	50 mm
Height	22 mm

Products for the electronic industry



Length with packaging	228 mm
Width with packaging	120 mm
Height with packaging	54 mm
Volume with packaging	1.417 dm ³
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
RoHS compliant	no
Surface	burnished
VDE	no
ESD compliant	no
Tool length	165 mm
AWG	1 / 0
Grip (expression)	With multi-component sheaths
Scissor type	cable shears
Cutting value copper cable, stranded	50 mm ²
Cutting value copper cable, stranded (diameter)	15 mm