

WT 1010, digital 1-channel soldering station, 95 W



This is soldering today

The detailed LC display provides an unprecedented overview of all functions, quickly and easily accessible via the new user-friendly menu button. The lightning-fast exchange of the heating element during operation makes it possible to work with several tips in quick succession. If a tip needs to be replaced, this is done independently of the heating element - which saves enormous costs.

Front-mounted power switch

The front-mounted power switch ensures easy operation at all times.

Multifunctional LC display

Unique LC display with detailed overview of all functions. Adjustable backlight. The power bar graph allows you to visually check the current power of the soldering station.

Convenient menu button

The new menu button ensures maximum user-friendliness and easy navigation in the menu structure.

Products for the electronic industry



Space-saving

The WT 1 / WT 1H can be stacked on top of the WTHA 1 to ensure more space at the workstation.

2-in-1 WSR tray

The plunger holder can be rotated 180°. The user can choose between wet and dry cleaning.

- WTP 90: The universal high-tech soldering iron with power-response soldering tip. Soldering tip family XNT & THM (large mass tips)
- locking function
- Display: LCD / Backlight
- equipotential bonding
- WT compatible

Item no.	WL37223
Model	WT 1010 Set
Model line	WT 1
Manufacturer	WELLER
Manufacturer article no.	T0053436699N
GPSR manufacturer data	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
Length	149 mm
Width	138 mm
Height	101 mm
Scope of delivery	1x 1-channel supply unit WT 1 1x WTP 90 soldering iron 1x soldering tip XNT A 1x change tool 1x WSR 200 safety rest 1x rubber rest 1x mains plug 1x instruction manual
Length in inches	5.87 in
Width in inches	5.43 in
Height in inches	3.98 in
Sales unit	1 set
Content unit	1 set
Frequency	50/60 Hz

Products for the electronic industry



Power	95 W
Voltage	230 V
Fuse	0.5 A
Temperature range °C	50 – 450 °C
Temperature range °F	150 – 850 °F
Temperature accuracy °F	±17 °F
Station (type)	soldering station
Included storage	WSR 200
Included soldering tip	XNT A
Included control unit	WT 1
Included soldering iron	WTP 90
Temperature stability °C	±2 °C
Temperature stability °F	±4 °F
ESD compliant	yes