WT 1010, digital 1-channel soldering station, 95 W

This is soldering today
The detailed LC display provides an unprecedented overview of all functions, quickly and easily accessible via the new user-friendly menu button. The lightning-fast exchange of the heating element during operation makes it possible to work with several tips in quick succession. If a tip needs to be replaced, this is done independently of the heating element - which saves enormous costs.

Front-mounted power switch
The front-mounted power switch ensures easy operation at all times.

Multifunctional LC display
Unique LC display with detailed overview of all functions. Adjustable backlight. The power bar graph allows you to visually check the current power of the soldering station.

Convenient menu button
The new menu button ensures maximum user-friendliness and easy navigation in the menu structure.

Products for the electronic industry

Space-saving
The WT 1 / WT 1H can be stacked on top of the WTHA 1 to ensure more space at the workstation.

2-in-1 WSR tray
The plunger holder can be rotated 180°. The user can choose between wet and dry cleaning.
• WTP 90: The universal high-tech soldering iron with power-response soldering tip. Soldering tip family XNT & THM (large mass tips)
• locking function
• Display: LCD / Backlight
• equipotential bonding
• WT compatible

item number	WL37223
model	WT 1010 Set
model line	WT 1
manufacturer	WELLER
manufacturer item number	T0053436699N
length	149 mm
width	138 mm
height	101 mm
scope of supply	1x 1-channel supply unit WT 1 1x WTP 90 soldering iron 1x soldering tip XNT A 1x change tool 1x WSR 200 safety rest 1x rubber rest 1x mains plug 1x instruction manual
length in inches	5.87 in
width in inches	5.43 in
height in inches	3.98 in
order unit	1 set
content unit	1 set
frequency	50/60 Hz
power	95 W
voltage	230 V
fuse	0.5 A

Products for the electronic industry

www.weidinger.eu

19.07.2024

temperature range °C	50 – 450 °C
temperature range °F	150 – 850 °F
temperature accuracy °F	±17 °F
station type	soldering station
included stand	WSR 200
included soldering tip	XNT A
included control unit	WT 1
included soldering iron	WTP 90
temperature stability °C	±2 °C
temperature stability °F	±4 °F
ESD safe	yes