

WT 1011H, digital 1-channel soldering station, 150 W



This is how soldering is done today

When 90 watts are not enough, the high-power version with 150 watts is the right solution. The new powerful WT soldering stations set new standards in user-friendliness. The detailed LC display provides a detailed overview of all functions - quickly and easily accessed via the new intuitive menu button. The lightning-fast exchange of the heating element during operation will in future enable work with several tips in quick change. If a tip needs to be replaced, this is done independently of the heating element - which saves enormous costs. The innovative 2-in-1 tray with rotatable plunger holder ensures a free choice between wet and dry cleaning. All stations of the WT-Line fit perfectly on top of each other, thus saving considerable space at the workplace.

Front-mounted power switch

The front-mounted power switch ensures easy operation at all times.

Multifunctional LC display

Unique LC display with detailed overview of all functions. Adjustable backlight. Power bar graph allows you to visually check the current power of the soldering station.







Products for the electronic industry





07.07.2025



Convenient menu button

The new menu button ensures maximum user-friendliness and easy navigation in the menu structure.

Space-saving

The WT 1/WT 1H can be stacked on top of the WTHA 1 to ensure more space at the workstation.

2-in-1 WSR tray

The piston holder can be rotated 180°. The user can choose between wet and dry cleaning.

- locking function
- Display: LCD / Backlight
- equipotential bonding
- WT compatible

item number	WL37250
model	WT 1011 Set
model line	WT 1H
manufacturer	WELLER
manufacturer item number	T0053439699N
GPSR manufacturer information	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
length	149 mm
width	138 mm
height	101 mm
scope of supply	1x 1-channel supply unit WT 1H 1x WP 200 soldering iron 1x soldering tip XHT D 1x WSR 202 safety rest 1x rubber rest 1x mains plug 1x instruction manual
length in inches	5.87 in
width in inches	5.43 in
height in inches	3.98 in
order unit	1 set
content unit	1 set











2/3



power	150 W
nominal power	150 W
voltage	230 V
temperature range °C	50 − 550 °C
temperature range °F	150 – 950 °F
temperature accuracy °F	±17 °F
station type	soldering station
included stand	WSR 202
included soldering tip	XHT D
included control unit	WT 1H
temperature stability °C	±2 °C
temperature stability °F	±4 °F
number of channels	1
ESD safe	yes









