

Soldering station TMT-2000S-PM, w/SHP-PM 100-240VAC



- Idle temperature stability: +/- 1.1 °C (2 °F)
- Maximum enclosure temperature: 50 °C (122 °F)
- Surface resistance: 105 - 109 Ω/sq
- Voltage soldering tip to ground: <2 mV
- No training required for calibration and use
- No additional costs for coil mounting
- Mains voltage: TMT-2000PS 100-240 VAC, 55W
- Resistance Soldering tip to ground:<2 Ohms DC
- Fuse: TMT-2000PS 250V 1A "Slo-Blo"
- Max. Power output: 50 Watt
- Output frequency: 470 KHz
- Curie heat technology - operating at 470 KHz
- replaces Metcal MFR-1110 systems

Item no.	WL37526
Model	TMT-2000S-PM
Manufacturer	THERMALTRONICS
Manufacturer article no.	TMT-2000S-PM
GPSR manufacturer data	Thermaltronics Castle Peak Road. 489491 HKG-999077 Sham Shui Po www.thermaltronics.com
Length	92 mm
Width	110 mm
Height	155 mm
Length with packaging	240 mm
Width with packaging	190 mm
Height with packaging	180 mm
Length with packaging in inches	9.4 in
Width with packaging in inches	7.5 in
Height with packaging in inches	7.1 in
Scope of delivery	1x TMT-2000PS supply unit 1x Handpiece SHP-PM 1x storage stand SHH-4 1x tip removal pad RMP-1 1x brass wool BC-1 1x cleaning sponge SPG-1 1x connecting cable CC-1
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Frequency	50/60 Hz
Power	50 W
Voltage	240 V
Matching tips	P-Series Tips
Included tray(s)	SHH-4
Included control unit	TMT-2000PS
Included handpiece	SHP-PM
Station (type)	soldering station
Included accessories	RMP-1 Protection cloth for tip removal, BC-1 Brass braiding, SPG-1 Sulfide-free sponge, CC-1 Connection cable

Ambient temperature (to)	50 °C
ESD compliant	yes

