

Soldering station TMT-5000S-2, w/SHP-T 220-240VAC



- Idle temperature stability: +/- 1.1 °C (2 °F)
- Maximum enclosure temperature: 50 °C (122 °F)
- Surface resistance: 105 - 109 Ω/sq
- Voltage soldering tip to ground: <2 mV
- No training required for calibration and use
- No additional costs for coil mounting
- Curie thermal technology - operation at 13.56 MHz
- Mains voltage: TMT-5000PS-2 220-240 VAC, 52W
- Resistance Soldering tip to ground: <2 Ohms DC
- Fuse: TMT-5000PS-2 250V 0.5A "Slo-Blo
- Max. Power output: 30 Watt
- Output frequency: 13.56 MHz
- compact, takes up very little working space

Item no.	WL37531
Model	TMT-5000S-2
Manufacturer	THERMALTRONICS
Manufacturer article no.	TMT-5000S-2
GPSR manufacturer data	Thermaltronics Castle Peak Road. 489491 HKG-999077 Sham Shui Po www.thermaltronics.com
Length	117 mm
Width	112 mm
Height	205 mm
Length with packaging	380 mm
Width with packaging	240 mm
Height with packaging	190 mm
Length with packaging in inches	15 in
Width with packaging in inches	9.4 in
Height with packaging in inches	7.5 in
Scope of delivery	1x TMT-5000PS supply unit 1x Handpiece SHP-T 1x SHH-2 storage stand 1x Soldering handpiece black handle SG-1-BK 1x soldering handpiece green handle SG-1-GR 1x tip removal pad RMP-1 1x brass wool BC-1 1x cleaning sponge SPG-1 1x connecting cable CC-1
Sales unit	1 piece
Content unit	1 piece
Frequency	50/60 Hz
Power	50 W
Voltage	240 V
Matching tips	T series
Station (type)	soldering station
Included accessories	RMP-1 Protection cloth for tip removal, SG-1-GR soldering handpiece green handle, SG-1-BK soldering handpiece, black handle, BC-1 brass braid, SPG-1 sulfide-free sponge, CC-1 connection cable
Included storage	SHH-2
Included control unit	TMT-5000PS

Included handpiece	SHP-T
ESD compliant	yes

