

## Soldering station TMT-9000S-2, w/SHP-1 220-240VAC



- Idle temperature stability: +/- 1.1 °C (2 °F)
- Maximum enclosure temperature: 50 °C (122 °F)
- Surface resistance: 105 - 109 Ω/sq
- Voltage soldering tip to ground: <2 mV
- No training required for calibration and use
- No additional costs for coil mounting
- Mains voltage: TMT-9000PS-2 220-240 VAC
- Resistance Soldering tip to ground: <2 Ohms
- Fuse: TMT-9000PS-2 250V 0.5A "Slo-Blo"
- Max. Power output: 40 Watt
- Output frequency: 13.56 MHz
- LCD display: 60mm x 16mm
- High thermal utilization and efficiency
- 13.56MHz power supply with integrated LCD display
- Two-stage solder ports

Products for the electronic industry



- replaces Metcal MX-500S-21

item number	<b>WL37535</b>
model	TMT-9000S-2
manufacturer	THERMALTRONICS
manufacturer item number	TMT-9000S-2
length	132 mm
width	118 mm
height	212 mm
length with packaging	380 mm
width with packaging	240 mm
height with packaging	190 mm
length with packaging in inches	15 in
width with packaging in inches	9.4 in
height with packaging in inches	7.5 in
scope of supply	1x TMT-9000PS supply unit 1x handpiece SHP-1 1x soldering tip M7CH176 1x SHH-1 storage stand 1x Soldering handpiece gray handle SG-1-GY 1x Soldering handpiece green handle SG-1-GR 1x Heat-resistant handle SG-1-HRB 1x Tip removal pad RMP-1 1x brass wool BC-1 1x Cleaning sponge SPG-1 1x Connecting cable CC-1
order unit	1 piece
content unit	1 piece
frequency	50/60 Hz
power	40 W
voltage	125 V
suitable tips	Series M
station type	soldering station
included accessories	RMP-1 Tip removal protection cloth, SG-1-GR soldering handpiece green handle, SG-1-GY soldering handpiece grey handle, BC-1 brass braid, SPG-1 sulfide free sponge
included stand	SHH-1
included soldering tip	M7CH176

included control unit	TMT-9000PS
included handpiece	SHP-1
ESD safe	yes

