

Soldering tip bevelled 45° 5,00mm (0,20"), only bevelled surface tinned



- For: TMT-2000S-K, TMT-2000PS, PS900 w/SHP-K, MFR-PS1100/MFR-PS2200 w/SHP-KM
- RoHS compliant / lead-free
- Top Series K / Series 600

| item number | WL37555 |
|----------------------------------|---------------------------------------|
| model | K60BVF050 |
| manufacturer | THERMALTRONICS |
| manufacturer item number | K60BVF050 |
| length with packaging | 117 mm |
| width with packaging | 33 mm |
| height with packaging | 13 mm |
| length with packaging in inches | 4.6 in |
| width with packaging in inches | 1.3 in |
| height with packaging in inches | 0.5 in |
| order unit | 1 piece |
| content unit | 1 piece |
| product series | K-Soldering tip series, 325°C - 358°C |
| temperature range °C | 325 – 358 °C |
| soldering tip or desoldering tip | soldering tip |
| tip length | 15 mm |
| tip length in inches | 0.59 in |
| tip width | 5 mm |
| tip width in inches | 0.2 in |
| tip shape | conical |
| tip alignment | sloped |

Products for the electronic industry





suitable handle

SHP-K, SHP-KM

Products for the electronic industry

