

## Soldering tip bevelled 45° 6,00mm (0,24"), only bevelled surface tinned

Gold Plated Connector

Stainless Steel Shaft

Lead-Free Tip



- For: TMT-2000S-K, TMT-2000PS, PS900 w/SHP-K, MFR-PS1100/MFR-PS2200 w/SHP-KM
- RoHS compliant / lead-free
- Top Series K / Series 600

<b>Item no.</b>	<b>WL37556</b>
Model	K60BVF060
Manufacturer	THERMALTRONICS
Manufacturer article no.	K60BVF060
GPSR manufacturer data	Thermaltronics Castle Peak Road. 489491 HKG-999077 Sham Shui Po www.thermaltronics.com
Length with packaging	117 mm
Width with packaging	33 mm
Height with packaging	13 mm
Length with packaging in inches	4.6 in
Width with packaging in inches	1.3 in
Height with packaging in inches	0.5 in
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Product series	K-Soldering tip series, 325°C - 358°C
Temperature range °C	325 – 358 °C
Soldering tip or desoldering tip	soldering tip
Tip series	K-series
Tip length	15 mm

Products for the electronic industry



Tip length in inches	0.59 in
Tip width	6 mm
Tip width in inches	0.24 in
Tip shape	conical
Tip alignment	sloped
Matching handpiece	SHP-K, SHP-KM
ESD compliant	no

