

## 30° 3.20mm (0.13") Chisel soldering tip

## Gold Plated Connector Stainless Steel Shaft Lead-Free Tip

- For: TMT-2000S-K, TMT-2000PS, PS900 w/SHP-K, MFR-PS1100/MFR-PS2200 w/SHP-KM
- RoHS compliant / lead-free
- Top Series K / Series 600

item number	WL37570
model	K60CH032A
manufacturer	THERMALTRONICS
manufacturer item number	K60CH032A
length with packaging	117 mm
width with packaging	33 mm
height with packaging	13 mm
length with packaging in inches	4.6 in
width with packaging in inches	1.3 in
height with packaging in inches	0.5 in
order unit	1 piece
content unit	1 piece
content unit product series	1 piece K-Soldering tip series, 325°C - 358°C
	·
product series	K-Soldering tip series, 325°C - 358°C
product series temperature range °C	K-Soldering tip series, 325°C - 358°C 325 – 358°C
product series temperature range °C soldering tip or desoldering tip	K-Soldering tip series, 325°C - 358°C 325 – 358 °C soldering tip
product series temperature range °C soldering tip or desoldering tip tip length	K-Soldering tip series, 325°C - 358°C 325 – 358°C soldering tip 10 mm
product series  temperature range °C  soldering tip or desoldering tip  tip length  tip length in inches	K-Soldering tip series, 325°C - 358°C  325 – 358 °C  soldering tip  10 mm  0.39 in
product series  temperature range °C  soldering tip or desoldering tip  tip length  tip length in inches  tip width	K-Soldering tip series, 325°C - 358°C  325 – 358 °C  soldering tip  10 mm  0.39 in  3.2 mm
product series  temperature range °C  soldering tip or desoldering tip  tip length  tip length in inches  tip width  tip width in inches	K-Soldering tip series, 325°C - 358°C  325 – 358 °C  soldering tip  10 mm  0.39 in  3.2 mm  0.13 in

Products for the electronic industry









