

## Soldering tip conical 1,0mm (0,04"), Power Plus

Gold Plated Connector	Stainless Steel Shaft	Lead-Free Ti
AND PROPERTY AND P	Description for the contraction of the forest terms of the contraction	

- For: TMT-9000S-1, TMT-9000S-2, MX-500, MX-5000, MX-5200
- Soldering tip series M
- RoHS compliant / lead-free

item number	WL37975
model	M8CS151H
manufacturer	THERMALTRONICS
manufacturer item number	M8CS151H
length with packaging	174 mm
width with packaging	35 mm
height with packaging	12 mm
length with packaging in inches	6.9 in
width with packaging in inches	1.4 in
height with packaging in inches	0.5 in
order unit	1 piece
content unit	1 piece
content unit product series	1 piece M-Soldering tip series, 420°C - 475°C
product series	M-Soldering tip series, 420°C - 475°C
product series temperature range °C	M-Soldering tip series, 420°C - 475°C 420 – 475°C
product series temperature range °C soldering tip or desoldering tip	M-Soldering tip series, 420°C - 475°C 420 – 475°C soldering tip
product series  temperature range °C  soldering tip or desoldering tip  tip length	M-Soldering tip series, 420°C - 475°C  420 – 475°C  soldering tip  15.4 mm
product series  temperature range °C  soldering tip or desoldering tip  tip length  tip length in inches	M-Soldering tip series, 420°C - 475°C  420 – 475 °C  soldering tip  15.4 mm  0.61 in
product series  temperature range °C  soldering tip or desoldering tip  tip length  tip length in inches  tip width	M-Soldering tip series, 420°C - 475°C  420 – 475 °C  soldering tip  15.4 mm  0.61 in  1 mm
product series  temperature range °C  soldering tip or desoldering tip  tip length  tip length in inches  tip width  tip width in inches	M-Soldering tip series, 420°C - 475°C  420 – 475 °C  soldering tip  15.4 mm  0.61 in  1 mm  0.04 in

Products for the electronic industry









