

## Soldering tip conical 0,40mm (0,016")



- Soldering tip series P
- for: TMT-2000PS, MFR-PS1100, MFR-PS2200, MFR-PS1K, MFR-PS2K
- RoHS compliant / lead-free

item number	WL38019
model	P75C004
manufacturer	THERMALTRONICS
manufacturer item number	P75C004
length with packaging	174 mm
width with packaging	35 mm
height with packaging	12 mm
length with packaging in inches	6.9 in
width with packaging in inches	1.4 in
height with packaging in inches	0.5 in
order unit	1 piece
content unit	1 piece
	·
product series	P-Soldering tip series, 350°C - 398°C
product series temperature range °C	
	P-Soldering tip series, 350°C - 398°C
temperature range °C	P-Soldering tip series, 350°C - 398°C 350 – 398°C
temperature range °C soldering tip or desoldering tip	P-Soldering tip series, 350°C - 398°C 350 – 398°C soldering tip
temperature range °C soldering tip or desoldering tip tip length	P-Soldering tip series, 350°C - 398°C 350 – 398 °C soldering tip 10.4 mm
temperature range °C soldering tip or desoldering tip tip length tip length in inches	P-Soldering tip series, 350°C - 398°C  350 – 398 °C  soldering tip  10.4 mm  0.41 in
temperature range °C soldering tip or desoldering tip tip length tip length in inches tip width	P-Soldering tip series, 350°C - 398°C  350 – 398 °C  soldering tip  10.4 mm  0.41 in  0.4 mm
temperature range °C soldering tip or desoldering tip tip length tip length in inches tip width tip width in inches	P-Soldering tip series, 350°C - 398°C  350 – 398 °C  soldering tip  10.4 mm  0.41 in  0.4 mm  0.02 in
temperature range °C soldering tip or desoldering tip tip length tip length in inches tip width tip width in inches	P-Soldering tip series, 350°C - 398°C  350 – 398 °C  soldering tip  10.4 mm  0.41 in  0.4 mm  0.02 in  conical











15.01.2025