

LED segment ring light



- photometric values depending on selected model
- dimensions control unit (LxWxH) 161 mm × 78 mm × 45 mm
- Length of supply cable approx. 0.8 m
- outer-Ø ring light 110 mm
- Height ring light 25,5 mm
- Inner diameter ring light 80 mm
- Clamping Ø max. 80 mm
- LED service life 50,000 h (manufacturer's specification)
- Weight ring light 220 g
- Input power supply (EUIUKIUS) 100 - 240 V AC, 50/60 Hz
- Output power supply 24 V DC, 1,000 mA
- Dimensions with packaging 320 mm × 205 mm × 95 mm
- Weight with packaging 780 g
- Max. power consumption 9 W
- Inner diameter 80 mm
- Outer diameter 110 mm

- Clamping diameter 80 mm
- internal thread M82 × 0.75
- Weight control unit 190 g
- Dimension packaging (L×W×H) 320 × 205 × 95 mm
- Dimension control unit (L×W×H) 161 × 78 × 45 mm

Item no.	WL38821
Model	RL5-80-S4
Manufacturer	STARLIGHT
Manufacturer article no.	100-010165
GPSR manufacturer data	STARLIGHT Opto-Electronics Flachslander Straße 8 DE-90431 Nürnberg www.starlight-sl.de
Height	25 mm
Sales unit	1 piece
Content unit	1 piece
Colour	dark grey, titanium
Material	anodised aluminium
Incl. battery	no
Light source	LED
(Optimal) working distance	75 mm
Number of LEDs	56
Working distance	50 - 140 mm
Internal thread	M82 x 0,75
Colour of light	pure white
Colour temperature	6500 °K
Cable length	1.4 m
Illuminant	16 x LED 5 mm