

## Three-arm turnstile for indoor use



### Description

Three arm turnstiles from Gunnebo help give your EPA a transparent and open character without losing sight of safety. Employees, for example, are given uncomplicated and quick access to the secured areas by means of a card reader, while unauthorised persons are denied access.

- Dimensions floor-standing enclosure: enclosure B = approx. 270 mm, foot H = approx. 950 mm, enclosure T = approx. 550 mm, passage B = approx. 530 mm
- Dimensions plywood: L = approx. 480 mm, passage B = approx. 530 mm
- Material: satin stainless steel, the turnstile can be controlled with any standard control unit.
- Power supply: 230Vac 50 Hz or 115Vac 60 Hz
- Rated power 50VA (Standby 5VA at Normal Off en)
- Operating temperature -5 to +50 °C (relative humidity 95%, non-condensing)
- IP protection class / MCBF / MTTR IP 32 / 10 million cycles (12 million for Normal Open) / less than 30 minutes
- Passage speed plug-in card reader: 20 passages per minute
- swipe card reader: 30 passages per minute
- Contactless transponder reader: 40 passages per minute
- Note: The price does not include the installation of the device.

## Product details

item number	<b>WL38841</b>
model	SlimStile BA
manufacturer	GUNNEBO
order unit	piece

