

Zero Smog TL extraction unit for soldering fumes, for 1-2 workstations, 190 m³/h at 3,000 Pa



- Economical extraction cleans the air at up to 2 workstations
- \bullet F7 fine dust pre-filter and extra-large HEPA H13 filter surface with 2.4 m 2 for particularly long filter service life
- Variable power control allows the extraction power to be adapted to specific requirements
- Low noise emission levels for quiet working areas
- Automatic filter change notification system
- Easy to operate and simple filter change
- Compatible with Easy Click 60 system for maximum flexibility. Adapts perfectly to the specific requirements of the workplace
- A WT Hub T0058768767 is required for connection to a WX or WT station
- Portable extraction unit, ideal for placement under the workbench or next to the workstation







Products for the electronic industry





1/2



item number	WL39780
model	ZERO-SMOG-TL
manufacturer	WELLER
manufacturer item number	FT91013699N
GPSR manufacturer information	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
length	335 mm
width	330 mm
height	445 mm
scope of supply	1x Zero Smog TL extraction unit 1x fine dust pre-filter F7 1x compact filter H13 1x operating instructions
order unit	1 piece
content unit	1 piece
frequency	50/60 Hz
power	120 W
fuse	T1,25A
voltage	230 V
fuse	1.25 A
vacuum max	3000 Pa
noise level	50 dBA
volume flow max	190 m ³ /h
filter type	compact filter
device series	Zero Smog TL
Type of vacuum generator	blower









2/2