

WT 1, digital 1-channel supply unit, 95 W



This is soldering today

The detailed LC display provides an unprecedented overview of all functions, quickly and easily accessible via the new user-friendly menu button. The lightning-fast exchange of the heating element during operation makes it possible to work with several tips in quick succession. If a tip needs to be replaced, this is done independently of the heating element - which saves enormous costs.

Front-mounted power switch

The front-mounted power switch ensures easy operation at all times.

Multifunctional LC display

Unique LC display with detailed overview of all functions. Adjustable backlight. The power bar graph allows you to visually check the current power of the soldering station.

Convenient menu button

Products for the electronic industry



The new menu button ensures maximum user-friendliness and easy navigation in the menu structure.

Space-saving

The WT 1 / WT 1H can be stacked on top of the WTHA 1 to ensure more space at the workstation.

2-in-1 WSR tray

The plunger holder can be rotated 180°. The user can choose between wet and dry cleaning.

- High functionality and flexibility - Numerous tools can be connected
- Automatic switch-off with integrated usage sensor in the tool
- Housing cover can be used as an additional shelf
- Intuitive operation through clear menu navigation
- Low space requirement thanks to stackability
- Graphic LC display with backlighting
- locking function
- equipotential bonding
- WT compatible

item number	WL40092
model	WT 1
model line	WT 1
manufacturer	WELLER
manufacturer item number	T0053434699N
length	149 mm
width	138 mm
height	101 mm
length in inches	5.87 in
width in inches	5.44 in
height in inches	3.98 in
order unit	1 piece
content unit	1 piece
power	95 W
voltage	230 V
fuse	0.5 A
temperature range °C	50 – 450 °C
temperature range °F	150 – 850 °F

Products for the electronic industry



temperature accuracy °F	±17 °F
temperature stability °C	±2 °C
temperature stability °F	±4 °F

