

## Unitec 2 work chair with castors, black fabric



The Unitec 2 work chair from Bimos is your ideal companion for daily use in production. It convinces with its price-performance ratio. The permanent contact backrest can be individually adjusted for sitting activities, and the work chair also has a large seat area.

- Backrest height adjustment
- plastic base

|                          |                                       |
|--------------------------|---------------------------------------|
| Item no.                 | WL40295                               |
| Model                    | 9653-CI01                             |
| Model line               | Unitec                                |
| Manufacturer             | BIMOS                                 |
| Manufacturer article no. | 9653-CI01                             |
| GPSR manufacturer data   | Bimos GmbH & Co. KG<br>Brühlstraße 21 |

Products for the electronic industry



|                             |                                                |
|-----------------------------|------------------------------------------------|
|                             | DE-72469 Meßstetten-Tieringen<br>www.bimos.com |
| Sales unit                  | 1 piece                                        |
| Content unit                | 1 piece                                        |
| Type (chair)                | castors                                        |
| Mechanics                   | Permanent contact mechanism                    |
| Upholstery colour           | black                                          |
| Upholstery material         | substance                                      |
| Five-foot cross             | yes                                            |
| Colour (chair frame)        | black                                          |
| Gas spring                  | yes                                            |
| Permanent contact mechanics | yes                                            |
| Seat height adjustment      | 440 – 620 mm                                   |
| ESD compliant               | no                                             |