

ESD low shoe FLASH 2005 XP, S1P, mesh, unisex, black/grey, size 45



The high-tech MESH UPPER encloses the foot precisely and guarantees the wearer lasting breathability, flexibility and unmistakable wearing comfort. The air texture of the fabric guarantees optimal air circulation and thus ensures a permanently pleasant foot climate.

ATLAS[®] brings together state-of-the-art technologies and the anatomical needs of every wearer. The new INNOFLEX SYSTEM[®] is a holistic running sole concept and supports the runner in every phase of movement. From the first to the last contact with the ground, the sole complex is permanently guided by the same, natural line of force, the INNOFLEX LINE. It optimally guides the forces from the heel to the toe and thus supports the natural line of force progression. Special areas such as the CLOUDZONE in the heel are responsible for the corresponding energy absorption, i.e. cushioning. The large-format tread surfaces, which are equipped with particularly energy-absorbing MPU[®] material, absorb the energy and return it to the movement process in a targeted manner. This





guarantees fatigue-free walking throughout the entire working day.

With the puncture-resistant XP[®] technology, ATLAS[®] offers an innovative system to protect the foot against sharp objects such as nails. A high-tech textile material containing aramid fibres is used for this purpose. The increased safety is not at the expense of wearing comfort, because the textile is metal-free, extremely light and supports the natural torsion of the foot.

Alu-tec[®] technology: The new lightness. Aluminium has not only served as a high-tech material in aviation and the automotive industry for years, but also in many ATLAS safety shoes today. The anatomically shaped aluminium toe cap is particularly light and shifts the centre of gravity of the shoe to the middle of the foot. This actively helps to prevent tripping accidents caused by imbalance. The thermally neutral behaviour of aluminium also prevents cold bridges from forming inside the shoe and thus guarantees a pleasant foot climate in all seasons.

Especially when kneeling, wear and tear can occur in the area of the shoe toe after some time. These can be significantly reduced with the help of the abrasion-resistant MPU toe protector and the service life of the shoe is thus increased.

Particularly in everyday working life, with high physical stress, temperature-regulating properties are not only required, but expected. The aktiv-X functional lining stands for the highest quality, innovative technology and offers the wearer permanent, active moisture regulation. The aktiv-X functional lining regulates moisture and ensures that the shoes dry again quickly. It does not stain, is skin-friendly and abrasion-resistant.

Work healthier with the right cushioning. The new 3D cushioning system from ATLAS[®] enables noticeably gentle and fatigue-free walking. The basis for this outstanding walking comfort is formed by three basic components: Pressure relief. Cushioning. Dynamics. This is ensured by the perfect interaction of a pressure-relieving insole and the light and responsive MPU sole technology.

The ATLAS[®] clima-stream[®] concept maximises breathability, balances moisture inside the shoe and optimally regulates the temperature of the environment. The use of high-quality, particularly breathable upper material, the thermoregulating inner lining and the Klima Komfort[®] insole ensures a unique wearing sensation.

geeignet für die Einlagenversorgung-DGUV 112-191

ATLAS[®] offers you a wide range of different orthopaedic insoles. The articles marked here are suitable for orthopaedic insoles according to DGUV regulation 112-191. The marking on the shoe is decisive for this.

• EN ISO 20345 S1P SRC





- ESD equipment
- also in W12 and in the special widths W13 and W14
- suitable for insole supply (DGUV 112-191)

modelFLASH 2005 XP ESDmodel lineFLASH 2005 XP ESDmanufacturerATLASmanufacturer item number43200-45GPSR manufacturer informationATLAS Schuhfabrik GmbH & Co.KG Frisher Lutt 159 DE-44319 Dortmund www.atlasschuhe.delength with packaging350 mmwidth with packaging350 mmorder unit1 pairconter unit1 paircolur manufacturerblack / greyColourgrey, blackmaterialMesh upper materialgenderunisexprotective capyesshoe secutionSNPSilp resistanceSPPuncture resistanceXPshoe widthW10 (standard width)features shoes'Mesh upper 'MPU INNOFLEX system 'MPU INNOFLEX system 'MPU INNOFLEX system 'MPU UNNOFLEX system 'AP metal-free penetration resistance -alu-tec aluminum toe cap ·MPU toe protection ·active-X tunctional lining ·active-X tunctional lining ·asticate for insoles-DGUV 112-191material shoesmesh upper	item number	WL40956	
manufacturerATLASmanufacturer item number43200-45GPSR manufacturer informationATLAS-Schuhfabrik GmbH & Co.KG Frische Luft 159GPSR manufacturer informationATLAS-Schuhfabrik GmbH & Co.KG Frische Luft 159length with packaging350 mmwidth with packaging250 mmheight with packaging150 mmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh upper materialgenderunisexprotective capyesshoe executionIow shoesafety classSIPSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoesNMPU INNOFLEX system · XPP metal-free penetration resistance · alu-tec aluminum toe cap · MPU INNOFLEX system · XPP metal-free penetration resistance · alu-tec aluminum toe cap · MPU INNOFLEX system · XPP metal-free penetration resistance · alu-tec aluminum toe cap · MPU INNOFLEX system · XPP metal-free penetration resistance · alu-tec aluminum toe cap · MPU toe protection · active-x functional lining · So cushoning system · Cluse-x functional lining · So cushoning system · So cushoning system · Sutable for insoles-DGUV 112-191	model	FLASH 2005 XP ESD	
manufacturer information43200-45GPSR manufacturer informationATLAS-Schuhfabrik GmbH & Co.KG Frische Luft 159 DE-4319 Dortmund www.atlasschuhe.delength with packaging350 mmwidth with packaging250 mmwidth with packaging150 mmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh upper materialgenderunisexprotective capyesshoe executionIow shoesafety classSIPSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoesMPU INNOFLEX systemshoe shoeSIPSupper features shoesMPU INNOFLEX systemshoe widthW10 (standard width)features shoesMPU INNOFLEX systemshoe widthMesh upper MPU INNOFLEX systemshoe widthMesh upper MPU INNOFLEX systemshoe widthMesh upper MPU INNOFLEX system MPU inter or cap MPU toe protection sative-X functional lining situable for insoles-DGUV 112-191	model line	FLASH 2005 XP ESD	
GPSR manufacturer informationATLAS-Schuhfabrik GmbH & Co.KG Frische Luft 159 DE-4319 Dortmund www.atlasschuhe.delength with packaging350 mmwidth with packaging250 mmheight with packaging150 mmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh upper materialgenderunisexprotective capyesshoe executionIow shoesafety classS1PSlip resistanceXP metal-free penetration protectionshoe widthV10 (standard width)features shoesMesh upperwidth Wtoe protection- Mesh uppershoe widthS1PSlip resistanceSPPuncture resistanceXP metal-free penetration protectionshoe width- Mesh upperweb upper- MPU INNOFLEX systemSlip resistance- Mesh uppershoe width- Mesh upperweb upper- MPU INNOFLEX systemshoe width- Mesh upperweb upper- MPU INNOFLEX systemshoe width- Mesh upperweb upper- MPU INNOFLEX systemshoe width- Mesh upperweb upper- MPU low portection- alu-tec aluminum toe cap- MPU toe protection- alu-tec aluminum toe cap- MPU toe protection- alu-tec aluminum toe cap- MPU toe protection- alu-tec aluminum toe cape- MPU toe protection- alu-tec al	manufacturer	ATLAS	
Frische Luft 159 DE-4319 Dortmund www.atlasschuhe.delength with packaging350 mmwidth with packaging250 mmheight with packaging150 mmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh upper materialgenderunisexprotective capyesshoe executionlow shoesafety classS1PSlip resistanceSRCPuncture resistanceSRCPuncture resistanceW10 (standard width)features shoes.Mesh upper .YDU INNOFLEX system .YD metal-free penetration resistance .alu-tec aluminum toe cap .MPU upor otection .acutive-X functional lining .3D cushioning system .clima-stream concept .suitable for insoles-DGUV 112-191	manufacturer item number	43200-45	
width with packaging250 mmheight with packaging150 mmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh upper materialgenderunisexprotective capyesshoe executionlow shoesafety classS1PSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes	GPSR manufacturer information	Frische Luft 159 DE-44319 Dortmund	
height with packaging150 mmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh upper materialgenderunisexprotective capyesshoe executionlow shoesafety classS1PSilp resistanceSRCPuncture resistanceSRCPuncture resistanceV10 (standard width)features shoes	length with packaging	350 mm	
order unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh upper materialgenderunisexprotective capyesshoe executionlow shoesafety classS1PShoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes.Mesh upper .MPU INNOFLEX systemshoe sole.Mesh upper .MPU innor free penetration resistanceshoe width.Mesh upper .MPU innofLEX systemshoe sole.Mesh upper 	width with packaging	250 mm	
content unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh upper materialgenderunisexprotective capyesshoe executionlow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthV10 (standard width)features shoesMPU INNOFLEX systemshoe soleSncSing resistanceSRCSupperMPU innofflex systemshoe widthS10 (standard width)features shoesMSH upper NPU innofflex systemshoe widthSing constraint free penetration resistance alu-te aluminum toe cap Sing constraint insig Sing cushioning system active-X functional lining Sing cushioning system	height with packaging	150 mm	
colour manufacturerblack / greyColourgrey, blackmaterialMesh upper materialgenderunisexprotective capyesshoe executionlow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes.MPU INNOFLEX systemshoe sole.MPU INNOFLEX systemSlip resistance.SRCPuncture resistance.MPU to genetration protectionshoe widthW10 (standard width)features shoes.MPU INNOFLEX system.SID resistance.MPU instance.SID resistance.SID resistance <td< td=""><td>order unit</td><td>1 pair</td></td<>	order unit	1 pair	
Colourgrey, blackmaterialMesh upper materialgenderunisexprotective capyesshoe executionlow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes.MPU INNOFLEX systemfeatures shoes.MPU INNOFLEX systemshoe widthS10 csandard width)features shoes.MPU toe protectionshoe width.Standard width)features shoes.MPU toe protectionshoe shoes.MPU toe protectionshoe shoes.Standard systemshoe shoes.Standard systemshoe width.Standard systemfeatures shoes.Standard systemshoe shoes.Standard system <tr< td=""><td>content unit</td><td>1 pair</td></tr<>	content unit	1 pair	
materialMesh upper materialgenderunisexprotective capyesshoe executionlow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes.Mesh upper .MPU INNOFLEX systemfeatures shoes.Mesh upper .MPU innoFLEX systemshoe width.Mesh upper .MPU innoFLEX system .XP metal-free penetration resistance .au-tec aluminum toe cap .MPU toe protection .active-X functional lining .3D cushioning system .clima-stream concept .suitable for insoles-DGUV 112-191	colour manufacturer	black / grey	
genderunisexprotective capyesshoe executionlow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes.Mesh upper .MPU INNOFLEX system .XP metal-free penetration resistance .AP metal-free penetration resistance .APU toe protection .active-X functional lining .3D cushioning system .clima-stream concept .clima-stream concept .clima-stream concept .clima-stream concept .clima-stream concept	Colour	grey, black	
protective capyesshoe executionlow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes. Mesh upper . MPU INNOFLEX system . XP metal-free penetration resistance . alu-tec aluminum toe cap . MPU toe protection . active-X functional lining . 3D cushioning system . clima-stream concept . suitable for insoles-DGUV 112-191	material	Mesh upper material	
shoe executionIow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes.Mesh upper .MPU INNOFLEX system .XP metal-free penetration resistance .alu-tec aluminum toe cap .MPU toe protection .active-X functional lining .3D cushioning system .clima-stream concept .sutable for insoles-DGUV 112-191	gender	unisex	
safety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes·Mesh upper ·MPU INNOFLEX system ·XP metal-free penetration resistance ·alu-tec aluminum toe cap ·MPU toe protection ·active-X functional lining ·3D cushioning system ·clima-stream concept ·sutable for insoles-DGUV 112-191	protective cap	yes	
shoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes• Mesh upper • MPU INNOFLEX system • XP metal-free penetration resistance • alu-tec aluminum toe cap • MPU toe protection • active-X functional lining • 3D cushioning system • clima-stream concept • suitable for insoles-DGUV 112-191	shoe execution	low shoe	
Slip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes• Mesh upper • MPU INNOFLEX system • XP metal-free penetration resistance • alu-tec aluminum toe cap • MPU toe protection • active-X functional lining • 3D cushioning system • clima-stream concept • suitable for insoles-DGUV 112-191	safety class	S1P	
Puncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes• Mesh upper • MPU INNOFLEX system • XP metal-free penetration resistance • alu-tec aluminum toe cap • MPU toe protection • active-X functional lining • 3D cushioning system • clima-stream concept • suitable for insoles-DGUV 112-191	shoe sole	MPU INNOFLEX system	
shoe width W10 (standard width) features shoes • Mesh upper • MPU INNOFLEX system • XP metal-free penetration resistance • alu-tec aluminum toe cap • MPU toe protection • active-X functional lining • 3D cushioning system • clima-stream concept • suitable for insoles-DGUV 112-191	Slip resistance	SRC	
features shoes• Mesh upper • MPU INNOFLEX system • XP metal-free penetration resistance • alu-tec aluminum toe cap • MPU toe protection • active-X functional lining • 3D cushioning system • clima-stream concept • suitable for insoles-DGUV 112-191	Puncture resistance	XP metal-free penetration protection	
 MPU INNOFLEX system XP metal-free penetration resistance alu-tec aluminum toe cap MPU toe protection active-X functional lining 3D cushioning system clima-stream concept suitable for insoles-DGUV 112-191 	shoe width	W10 (standard width)	
material shoes mesh upper	features shoes	 MPU INNOFLEX system XP metal-free penetration resistance alu-tec aluminum toe cap MPU toe protection active-X functional lining 3D cushioning system clima-stream concept 	
	material shoes	mesh upper	

material shoes





shoe size EU	45
ESD safe	yes
Category (PPE Regulation)	Category 2

Other versions

item number	shoe size EU	shoe width
WL40947	36	W10 (standard width)
WL57023	36	W12
WL40948	37	W10 (standard width)
WL57024	37	W12
WL40949	38	W10 (standard width)
WL57025	38	W12
WL40950	39	W10 (standard width)
WL57026	39	W12
WL40951	40	W10 (standard width)
WL57027	40	W12
WL40952	41	W10 (standard width)
WL57028	41	W12
WL40953	42	W10 (standard width)
WL57029	42	W12
WL40954	43	W10 (standard width)
WL57030	43	W12
WL40955	44	W10 (standard width)
WL57031	44	W12
WL40956	45	W10 (standard width)
WL57032	45	W12
WL40957	46	W10 (standard width)
WL57033	46	W12
WL40958	47	W10 (standard width)
WL57034	47	W12
WL40959	48	W10 (standard width)
WL57035	48	W12
WL40960	49	W10 (standard width)





WL57036

49

W12

