

ESD low shoe FLASH 2005 XP, S1P, mesh, unisex, black/grey, size 46



The high-tech MESH UPPER encloses the foot precisely and guarantees the wearer lasting breathability, flexibility and unmistakable wearing comfort. The air texture of the fabric guarantees optimal air circulation and thus ensures a permanently pleasant foot climate.

ATLAS[®] brings together state-of-the-art technologies and the anatomical needs of every wearer. The new INNOFLEX SYSTEM[®] is a holistic running sole concept and supports the runner in every phase of movement. From the first to the last contact with the ground, the sole complex is permanently guided by the same, natural line of force, the INNOFLEX LINE. It optimally guides the forces from the heel to the toe and thus supports the natural line of force progression. Special areas such as the CLOUDZONE in the heel are responsible for the corresponding energy absorption, i.e. cushioning. The large-format tread surfaces, which are equipped with particularly energy-absorbing MPU[®] material, absorb the energy and return it to the movement process in a targeted manner. This





guarantees fatigue-free walking throughout the entire working day.

With the puncture-resistant XP[®] technology, ATLAS[®] offers an innovative system to protect the foot against sharp objects such as nails. A high-tech textile material containing aramid fibres is used for this purpose. The increased safety is not at the expense of wearing comfort, because the textile is metal-free, extremely light and supports the natural torsion of the foot.

Alu-tec[®] technology: The new lightness. Aluminium has not only served as a high-tech material in aviation and the automotive industry for years, but also in many ATLAS safety shoes today. The anatomically shaped aluminium toe cap is particularly light and shifts the centre of gravity of the shoe to the middle of the foot. This actively helps to prevent tripping accidents caused by imbalance. The thermally neutral behaviour of aluminium also prevents cold bridges from forming inside the shoe and thus guarantees a pleasant foot climate in all seasons.

Especially when kneeling, wear and tear can occur in the area of the shoe toe after some time. These can be significantly reduced with the help of the abrasion-resistant MPU toe protector and the service life of the shoe is thus increased.

Particularly in everyday working life, with high physical stress, temperature-regulating properties are not only required, but expected. The aktiv-X functional lining stands for the highest quality, innovative technology and offers the wearer permanent, active moisture regulation. The aktiv-X functional lining regulates moisture and ensures that the shoes dry again quickly. It does not stain, is skin-friendly and abrasion-resistant.

Work healthier with the right cushioning. The new 3D cushioning system from ATLAS[®] enables noticeably gentle and fatigue-free walking. The basis for this outstanding walking comfort is formed by three basic components: Pressure relief. Cushioning. Dynamics. This is ensured by the perfect interaction of a pressure-relieving insole and the light and responsive MPU sole technology.

The ATLAS[®] clima-stream[®] concept maximises breathability, balances moisture inside the shoe and optimally regulates the temperature of the environment. The use of high-quality, particularly breathable upper material, the thermoregulating inner lining and the Klima Komfort[®] insole ensures a unique wearing sensation.

geeignet für die Einlagenversorgung-DGUV 112-191

ATLAS[®] offers you a wide range of different orthopaedic insoles. The articles marked here are suitable for orthopaedic insoles according to DGUV regulation 112-191. The marking on the shoe is decisive for this.

• EN ISO 20345 S1P SRC





- ESD equipment
- also in W12 and in the special widths W13 and W14
- suitable for insole supply (DGUV 112-191)

modelFLASH 2005 XP ESDmodel lineFLASH 2005 XP ESDmanufacturerATLASmanufacturer item number43200-46GPSR manufacturer informationATLAS Schuhfabrik GmbH & Co.KG Frische Luft 159 DE-44319 Dottmund www.atlasschuhe.delength with packaging350 nmwidth with packaging250 nmheight with packaging150 nmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh uppergenderunisexprotective capyesshoe executionlow shoesafety classSIPSlip resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes	item number	WL40957	
manufacturerATLASmanufacturer item number43200-46GPSR manufacturer informationATLAS-Schuhfabrik GmbH & Co.KG Frische Luft 159 Dortmund www.atlasschuhe.delength with packaging350 mmwidth with packaging250 mmheight with packaging150 mmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh uppergenderunisexprotective capyesshoe executionlow shoesafety classSIPSlip resistanceSRCPuncture resistanceMPU INNOFLEX systemshoe widthW10 (standard width)features shoes'Mesh upperuniters and widthSiD cushioning systemshoe soleSDC content in ing > SiD cushioning systemshoe widthUnschuer capshoe widthSiD sole Sole SoleSub executionSiD cushioning systemshoe widthinder sign systemfeatures shoes'MPU INNOFLEX system'MPU INNOFLEX system'MPU innof-LEX system'MPU INNOFLEX system'MPU innof-LEX system'SD cushioning ing system'SD cushioning system'cima-stream concept'suitable for i	model	FLASH 2005 XP ESD	
manufacturer information43200-46GPSR manufacturer informationATLAS-Schuhfabrik GmbH & Co.KG Frische Luft 159 DE-44319 Dortmund www.atlasschuhe.delength with packaging350 mmwidth with packaging250 mmwidth with packaging150 mmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh uppergenderunisexprotective capyesshoe executionIow shoesafety classS1PSlip resistanceSXCPuncture resistanceXP metal-free penetration protectionshoe soleW10 (standard width)features shoesMesh uppershoe soleXP metal-free penetration protectionshoe widthV10 (standard width)features shoesMPU INNOFLEX systemshoe widthMesh upperwPU INNOFLEX system*XP metal-free penetration protectionshoe widthW10 (standard width)features shoesMPU INNOFLEX systemshoe widthMesh upperwPU inno cape*Mesh upperwPU inno FLEX system*XP metal-free penetration resistancesalter caluminum toe cape*MPU iop protectionsatisbe for insoles-DGUV 112-191*SD cushioning system	model line	FLASH 2005 XP ESD	
GPSR manufacturer informationATLAS-Schuhfabrik GmbH & Co.KG Frische Luft 159 DE-44319 Dortmund www.atlasschuhe.delength with packaging350 mmwidth with packaging250 mmheight with packaging150 mmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh uppergenderunisexprotective capyesshoe executionIow shoesafety classS1PSlip resistanceXP metal-free penetration protectionshoe widthVIO (standard width)features shoesMesh upperwidth With packagingS1D mcshoe shoeS1Pshoe calculation protectionXP metal-free penetration protectionshoe widthVIO (standard width)features shoesMPU INNOFLEX systemshoe widthMesh upperwidth with packagingMesh upperwidth with packagingMesh uppershoe widthVIO (standard width)features shoesMPU INNOFLEX system resistance - alu-fea eluminum toe cap - MPU ion protection - active-X functional lining - active-X functional lining - active-X functional lining - active-X functional lining - suitable for insoles-DGUV 112-191	manufacturer	ATLAS	
Frische Luft 159 DE-4319 Dortmund www.atlasschuhe.delength with packaging350 mmwidth with packaging250 mmheight with packaging150 mmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh uppergenderunisexprotective capyesshoe executionlow shoesafety classS1PSlip resistanceSRCPuncture resistanceSRCPuncture resistanceW10 (standard width)features shoes.Mesh uppershoe sulth Puncture resistance.Mesh uppershoe unith Puncture resistance.Mesh uppershoe unithU10 (standard width)features shoes.Mesh uppershoe sulth Puncture resistance.Mesh uppershoe unith.Dueshioning systemshoe unithU10 (standard width)features shoes.Mesh uppershoe shoes.Mesh uppershoe shoes.Mesh uppershoe widthU10 (standard width)features shoes.Mesh upper.Shoe shoes.Mesh upper<	manufacturer item number	43200-46	
width with packaging250 mmheight with packaging150 mmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh uppergenderunisexprotective capyesshoe executionlow shoesafety classS1PSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes	GPSR manufacturer information	Frische Luft 159 DE-44319 Dortmund	
height with packaging150 mmorder unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh uppergenderunisexprotective capyesshoe executionlow shoesafety classS1PSilp resistanceSRCPuncture resistanceSRCPuncture resistanceW10 (standard width)features shoesMPU INNOFLEX system ·XP metal-free penetration resistance ·AP metal-free penetration resistance ·AP metal-free penetration resistance 	length with packaging	350 mm	
order unit1 paircontent unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh uppergenderunisexprotective capyesshoe executionlow shoesafety classS1PSilp resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes.Mesh upper.MPU INNOFLEX system.XP metal-free penetration resistance.MPU INNOFLEX system.XP metal-free penetration resistance.MPU INNOFLEX system.XP metal-free penetration resistance.MPU INNOFLEX system.XP metal-free penetration resistance.alu-tec aluminum toe cap .MPU toe protection.AUV or protection.alu-tec aluminum toe cap .AMPU toe protection.AUV or protection.alu-tec aluminum toe cap .AMPU toe protection.AUV or protection.attive-X functional lining .3D cushining system .clima-stream concept .suitable for insoles-DGUV 112-191	width with packaging	250 mm	
content unit1 paircolour manufacturerblack / greyColourgrey, blackmaterialMesh uppergenderunisexprotective capyesshoe executionlow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes.Mesh upper .MPU INNOFLEX systemshoe sole.Mesh upper .MPU innofectionshoe width.Mesh upper .MPU innofectionfeatures shoes.Mesh upper .MPU innofectionshoe sole.Mesh upper .Ar metal-free penetration resistance .alu-te aluminum toe cap .MPU toe protection .active-X functional lining .3D cushioning system .clima-stream concept .suitable for insoles-DGUV 112-191	height with packaging	150 mm	
colour manufacturerblack / greyColourgrey, blackmaterialMesh uppergenderunisexprotective capyesshoe executionlow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes.MPU INNOFLEX systemshoe sole.MPU INNOFLEX systemshoe widthS10 csahard width)features shoes.Mesh upper .MPU innofLex systemshoe width.MPU innofLex system .Strem epenetration resistance .alu-tec aluminum toe cap .MPU toe protection .active-X functional lining .3D cushioning system .clima-stream concept .suitable for insoles-DGUV 112-191	order unit	1 pair	
Colourgrey, blackmaterialMesh uppergenderunisexprotective capyesshoe executionlow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes.MPU INNOFLEX systemshoe sole.MPU INNOFLEX systemshoe widthW10 (standard width)features shoes.Mesh upper .MPU INNOFLEX system .system .systemshoe width.MPU toe protection .active-X functional lining .3D cushioning system .clima-stream concept .suitable for insoles-DGUV 112-191	content unit	1 pair	
materialMesh uppergenderunisexprotective capyesshoe executionlow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes.Mesh upper .MPU INNOFLEX systemfeatures shoes.Mesh upper .XP metal-free penetration resistance .au-tec aluminum toe cap .MPU toe protection .active-X functional lining .3D cushioning system .clima-stream concept .suitable for insoles-DGUV 112-191	colour manufacturer	black / grey	
genderunisexprotective capyesshoe executionlow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes.Mesh upper .MPU INNOFLEX system .XP metal-free penetration resistance .AP uncture resistanceshoe width.Mesh upper .MPU INNOFLEX system .XP metal-free penetration resistance .alu-tec aluminum toe cap .MPU toe protection .active-X functional lining .3D cushioning system .clima-stream concept .suitable for insoles-DGUV 112-191	Colour	grey, black	
protective capyesshoe executionlow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes. Mesh upper . MPU INNOFLEX system . XP metal-free penetration resistance . alu-tec aluminum toe cap . MPU toe protection . active-X functional lining . 3D cushioning system . clima-stream concept . usuable for insoles-DGUV 112-191	material	Mesh upper	
shoe executionIow shoesafety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes· Mesh upper · MPU INNOFLEX system · XP metal-free penetration resistance · alu-tec aluminum toe cap · MPU toe protection · active-X functional lining · 3D cushioning system · clima-stream concept · suitable for insoles-DGUV 112-191	gender	unisex	
safety classS1Pshoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes· Mesh upper · MPU INNOFLEX system · XP metal-free penetration resistance · alu-tec aluminum toe cap · MPU toe protection · active-X functional lining · 3D cushioning system · clima-stream concept · suitable for insoles-DGUV 112-191	protective cap	yes	
shoe soleMPU INNOFLEX systemSlip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes• Mesh upper • MPU INNOFLEX system • XP metal-free penetration resistance • alu-tec aluminum toe cap • MPU toe protection • active-X functional lining • 3D cushioning system • clima-stream concept • suitable for insoles-DGUV 112-191	shoe execution	low shoe	
Slip resistanceSRCPuncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes• Mesh upper • MPU INNOFLEX system • XP metal-free penetration resistance • alu-tec aluminum toe cap • MPU toe protection • active-X functional lining • 3D cushioning system • clima-stream concept • suitable for insoles-DGUV 112-191	safety class	S1P	
Puncture resistanceXP metal-free penetration protectionshoe widthW10 (standard width)features shoes• Mesh upper • MPU INNOFLEX system • XP metal-free penetration resistance • alu-tec aluminum toe cap • MPU toe protection • active-X functional lining • 3D cushioning system • clima-stream concept • suitable for insoles-DGUV 112-191	shoe sole	MPU INNOFLEX system	
shoe width W10 (standard width) features shoes • Mesh upper • MPU INNOFLEX system • XP metal-free penetration resistance • alu-tec aluminum toe cap • MPU toe protection • active-X functional lining • 3D cushioning system • clima-stream concept • suitable for insoles-DGUV 112-191	Slip resistance	SRC	
features shoes• Mesh upper • MPU INNOFLEX system • XP metal-free penetration resistance • alu-tec aluminum toe cap • MPU toe protection • active-X functional lining • 3D cushioning system • clima-stream concept • suitable for insoles-DGUV 112-191	Puncture resistance	XP metal-free penetration protection	
 MPU INNOFLEX system XP metal-free penetration resistance alu-tec aluminum toe cap MPU toe protection active-X functional lining 3D cushioning system clima-stream concept suitable for insoles-DGUV 112-191 	shoe width	W10 (standard width)	
material shoes mesh upper	features shoes	 MPU INNOFLEX system XP metal-free penetration resistance alu-tec aluminum toe cap MPU toe protection active-X functional lining 3D cushioning system clima-stream concept 	
	material shoes	mesh upper	

material shoes





shoe size EU	46
ESD safe	yes
Category (PPE Regulation)	Category 2

Other versions

item number	shoe size EU	shoe width
WL40947	36	W10 (standard width)
WL57023	36	W12
WL40948	37	W10 (standard width)
WL57024	37	W12
WL40949	38	W10 (standard width)
WL57025	38	W12
WL40950	39	W10 (standard width)
WL57026	39	W12
WL40951	40	W10 (standard width)
WL57027	40	W12
WL40952	41	W10 (standard width)
WL57028	41	W12
WL40953	42	W10 (standard width)
WL57029	42	W12
WL40954	43	W10 (standard width)
WL57030	43	W12
WL40955	44	W10 (standard width)
WL57031	44	W12
WL40956	45	W10 (standard width)
WL57032	45	W12
WL40957	46	W10 (standard width)
WL57033	46	W12
WL40958	47	W10 (standard width)
WL57034	47	W12
WL40959	48	W10 (standard width)
WL57035	48	W12
WL40960	49	W10 (standard width)





WL57036

49

W12

