Crimping pliers for wire end ferrules, insulated, VDE tested, 0.25 - 2.5 mm², 145 mm



Crimping pliers for wire end ferrules For crimping wire end ferrules DIN 46228 part 1 + 4 in the range of 0.25 to 2.5 mm². Crimping in marked trapezoidal profiles for secure connection of sleeve and conductor. - Application: Wire end ferrules - Capacity square millimetres: 0.25 - 2.5mm² - Number of nests: 4 - AWG: 23 - 13.

- For crimping wire end ferrules DIN 46228 part 1 + 4 in the range of 0.25 to 2.5 mm².
- Crimping in marked trapezoidal profiles for secure connection of sleeve and conductor

item number	WL41562
model	97 68 145 A
manufacturer	KNIPEX
manufacturer item number	97 68 145 A
length	145 mm
width	55 mm
height	25 mm
length with packaging	177 mm
width with packaging	61 mm
height with packaging	30 mm
Packaging volume	0.315 dm³
order unit	1 piece

content unit	1 piece
type of packaging	single pack
standards	DIN EN 60900 | IEC 60900
RoHS conform	no
VDE	yes
application crimp	Wire end ferrules
Number of crimp nests	4
crimp profile	Trapezoidal crimp
tool length	145 mm
AWG	23 - 13
type of handle	insulated with multi-component sleeves, VDE-tested
type of pliers	crimping pliers