

Cable shears, with anti-trap protection, plastic-coated handles, Ø 15 mm / 50 mm², 165 mm



For cutting copper and aluminium cables, solid and stranded. Cuts smoothly and cleanly without crushing. Not suitable for steel wire and hard-drawn copper conductors. Hardened cutting edges with precision grinding. Easy cutting with one-hand operation. With clamping protection. Adjustable screw joint, self-locking. - Shape: 1 - Cutting value Cu-cable, stranded: 50mm² - Cutting value Cu-cable, stranded: Ø 15mm - AWG: 1 / 0

- For cutting Cu and Al cables, solid and stranded
- Cuts smoothly and cleanly without crushing
- Not suitable for steel wire and hard drawn copper conductors
- Hardened cutting edges with precision grinding
- Easy cutting with one hand operation
- With clamping protection
- Adjustable screw joint, self-locking

item number	WL41799
model	95 11 165
manufacturer	KNIPEX
manufacturer item number	95 11 165
length	170 mm
width	42 mm
height	14 mm
length with packaging	213 mm
width with packaging	75 mm
height with packaging	49 mm

Products for the electronic industry



Packaging volume	0.783 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	Insulation standard: IEC 60900 DIN EN 60900
RoHS conform	no
surface	burnished
VDE	no
ESD safe	no
tool length	165 mm
AWG	1 / 0
type of handle	Covered with plastic
type of shears	cable shears
Cutting value copper cable, multistranded	50 mm ²
Cutting value copper cable, multistranded (diameter)	15 mm