

System luminaire TAMETO - SAHQ 88 D, mounting top/fixed, through-wired



The Tameto system luminaire from Waldmann is convincing on many levels: Maintenance-free LED technology, extremely homogeneous, glare-free and flicker-free light as well as light emission with a cone prism structure for perfect glare control. The Tameto system luminaire is available in various lengths for different desk widths and lighting requirements to equip the perfect industrial workplace. The robust aluminium housing and enclosed design protect the inside of the system luminaire and work surface from contamination.

- Control gear: Electronic ballast
- Connected load: 220-240 V, 50/60 Hz
- Luminaire luminous flux: 3200 lm
- Luminaire luminous efficacy: approx. 87 lm/W
- Light colour: neutral white
- Colour rendering (Ra): >80
- glare control: conical prismatic shield
- Technology: switchable
- Operation: rocker switch
- Mains cable: approx. 0.3 m; junction box, connecting plugGST 18i3S
- Mounting: Screw-on bracket
- Length: 1256 mm
- Special feature: through-wired
- Em: 1071 lx, Emax: 1448 lx, Emin: 659 lx

item number	WL41841
model	SAHQ 88 D
manufacturer	WALDMANN
manufacturer item number	112979000-00555694

Products for the electronic industry



length	1300 mm
width	220 mm
depth	120 mm
order unit	1 piece
content unit	1 piece
Lamp or magnifier type	system light
luminous flux	3200 lm
connections	220-240 V; 50/60 Hz
colour temperature	4000 °K
power	33 W
equipping	LED, energy efficiency class A+
attachment	Ceiling mounting
housing colour	Aluminium/plastic, anodised, aluminium coloured (colourless anodised)
protection class	1
protection class	20 IP
ESD safe	no