

PVC floor tile, T-Lock, gray, 500 x 500 x 10 mm, 4 pieces



Ecotile's interlocking industrial tiles are suitable as floor tiles for commercial, domestic and light industrial applications to reduce dust and noise. The application should take place on hard surfaces. The floor tiles consist of an injection-moulded composite material that is ecologically sustainable.

Important: Please note the installation instructions for ecotile floor tiles. These instructions are available under "Documents" > "Download technical data sheet".

- is laid loose and has an open dovetail connection for quick installation
- no pre-treatment of the substrate necessary
- Heavy duty flooring - can withstand high point loads, impacts and vibrations
- suitable for heavy pedestrian and vehicle traffic and fork-lift trucks
- 100% recyclable PVC
- injection-moulded
- chemical resistance
- good thermal and acoustic insulation

| | |
|-------------------------------|---|
| item number | WL41926 |
| model | ecotile Flooring |
| manufacturer | ECOTILE |
| manufacturer item number | E500/10/221 |
| GPSR manufacturer information | ecotile Flooring Sedgwick Road Unit 15 GB-LU4 9DT Luton www.ecotileflooring.com |

| | |
|---------------------|-----------------|
| length | 500 mm |
| width | 500 mm |
| height | 10 mm |
| order unit | 1 PU |
| content unit | 4 piece |
| colour manufacturer | gray (RAL 7015) |
| Colour | grey |
| material | pvc |
| Interlocking system | T-Lock |
| surface texture | flat |
| Strength | 10 mm |
| type of lining | floor tile |
| properties lining | smooth |
| ESD safe | no |

Other versions

| item number | Strength |
|----------------|--------------|
| WL41850 | 7 mm |
| WL41926 | 10 mm |