

## ESD Electronic-Super-Knips XL, side cutter for fiberglass, 140 mm



Electronic Super Knips® XL ESD Additional 15 mm longer version: higher stability, higher cutting performance. Precision-ground cutting edges without facet for precise and flush cutting of the finest wires, e.g. in electronics and precision mechanics. Precisely shaped tips also cut adjacent wires from Ø 0.2 mm. With opening spring and opening limiter for comfortable, ergonomic and fast work due to automatic opening and comfortable leg width. Extremely easy movement for low-fatigue work due to precise joint with stainless steel rivet. Highly durable, made of burnished special tool steel, cutting edges additionally inductively hardened to 64 HRC. - cutting values medium hard wire (diameter): Ø 1,4mm - cutting values soft wire (diameter): Ø 0,2 - 2,1mm - jaw length (B): 12,3mm - jaw thickness (at joint) (D): 9,2mm - head width (A): 15,7mm - ESD: Yes

- Precision-ground cutting edges without facet for precise and flush cutting of the finest wires, e.g. for electronics and precision mechanics
- Exactly shaped tips also cut adjacent wires from Ø 0.2 mm
- With opening spring and opening limiter for comfortable, ergonomic and fast work due to automatic opening and comfortable leg width
- Extremely smooth action for fatigue-free working due to precise joint with stainless steel rivet

item number	WL42005
model	78 61 140 ESD
manufacturer	KNIPEX
manufacturer item number	78 61 140 ESD
length	142 mm

Products for the electronic industry



width	83 mm
height	14 mm
length with packaging	213 mm
width with packaging	75 mm
height with packaging	49 mm
Packaging volume	0.783 dm <sup>3</sup>
order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	DIN EN 61 340-5, DIN ISO 9654
product series	Electronic-Super-Knips®
RoHS conform	no
surface	burnished
VDE	no
Cut form	without bevel
ESD safe	yes
tool length	140 mm
type of side cutter	side cutter
type of handle	with multi-component handles
cutting value wire diameter medium	1.4 mm
cutting value wire diameter soft	2.1 mm