

ESD spiral cable, 1 MOhm, yellow, 1.8 m, 10/10 mm push button



The ESD spiral cable from Safeguard is an important component for earthing people in the ESD zone (EPA) to protect electronic devices and components from electrostatic discharge. The leakage resistance is 1 Mohm. The length of the cable of 1.8 meters allows flexible working without restricting freedom of movement. The ESD spiral cable in yellow has 2x 10 mm press studs. The colour allows the cable to be easily identified at all times and in different lighting conditions.

- 1 MOhm
- 1,8 m
- tested according to BGI 818: 2001

Item no.	WL42062
Model	SG-SK-10/10DK-GE-1800mm-1Mohm
Manufacturer	SAFEGUARD
Manufacturer article no.	SG-SK-10/10DK-GE-1800MM-1MOHM
GPSR manufacturer data	Weidinger GmbH Hertha-Sponer-Str. 1a DE-82216 Gernlinden
Length	1800 mm
Sales unit	1 piece

Products for the electronic industry



Content unit	1 piece
Manufacturer colour information	yellow
Colour	yellow
Incl. battery	no
Connection 1	Push button: Ø 3mm
Connection 2	Push button: Ø 10mm
Electrical resistance	1 MΩ
Connection	10 / 10 mm press stud
ESD certification according to IEC 61340-5-1	yes
ESD compliant	yes
Certified according to BGI818	yes

Other versions

Item no.	Length
WL42062	1800 mm
WL42069	2400 mm
WL42077	3600 mm