

ESD spiral cable, 1 MOhm, black, 3.6 m, 10/10 mm push button



The ESD spiral cable from Safeguard is an important component for earthing people in the ESD zone (EPA) to protect electronic devices and components from electrostatic discharge. The leakage resistance is 1 Mohm. The length of the cable of 3.6 meters allows flexible working without restricting freedom of movement. The ESD spiral cable in black has 2x 10 mm press studs. The colouring makes it easy to see the cable at all times and in different lighting conditions.

- 1 Mohm
- 3,6 m
- tested according to BGI 818: 2001

item number	WL42076
model	SG-SK-10/10DK-SCH-3600mm-1Mohm
manufacturer	SAFEGUARD
manufacturer item number	SG-SK-10/10DK-SCH-3600MM-1MOHM
GPSR manufacturer information	Weidinger GmbH Hertha-Sponer-Str. 1a DE-82216 Gernlinden
length	3600 mm
order unit	1 piece
content unit	1 piece

Products for the electronic industry



colour manufacturer	black
Colour	black
Connection 1	Push button: Ø 10mm
Connection 2	Push button: Ø 10mm
Electrical resistance	1 MΩ
connection	10 / 10 mm press stud
ESD safe	yes
Certification acc. to BGI818	yes

Other versions

item number	length
WL24074	1800 mm
WL42068	2400 mm
WL42076	3600 mm

