

## ESD spiral cable, 2 MOhm, black, 1.8 m, 10/10 mm push button



The ESD spiral cable from Safeguard is an important component for earthing people in the ESD zone (EPA) to protect electronic devices and components from electrostatic discharge. The leakage resistance is 2 Mohm. The length of the cable of 1.8 meters allows flexible working without restricting freedom of movement. The ESD spiral cable in black has 2x 10 mm press studs. The colouring makes it easy to identify the cable at all times and in different lighting conditions.

- 2 MOhm
- 1,8 m
- tested according to BGI 818: 2001

<b>Item no.</b>	<b>WL42081</b>
Model	SG-SK-10/10DK-SCH-1800mm-2Mohm
Manufacturer	SAFEGUARD
Manufacturer article no.	SG-SK-10/10DK-SCH-1800MM-2MOHM
GPSR manufacturer data	Weidinger GmbH Hertha-Sponer-Str. 1a DE-82216 Gernlinden
Length	1800 mm
Sales unit	1 piece
Content unit	1 piece

Products for the electronic industry



Manufacturer colour information	black
Colour	black
Incl. battery	no
Connection 1	Push button: Ø 10mm
Connection 2	Push button: Ø 10mm
Electrical resistance	2 MΩ
Connection	10 / 10 mm press stud
ESD certification according to IEC 61340-5-1:2016	yes
ESD compliant	yes
Certified according to BGI818	yes

## Other versions

Item no.	Length
<b>WL42081</b>	<b>1800 mm</b>
WL19687	2400 mm
WL42428	3600 mm