

ESD spiral cable, 2 MOhm, yellow, 2.4 m, 3/10 mm push-button



The ESD spiral cable from Safeguard is an important component in personal grounding in the ESD zone (EPA) to protect electronic equipment and components from electrostatic discharge. The leakage resistance is 2 MOhm. The length of the cable of 2.4 meters allows flexible working without restricting the freedom of movement. The ESD spiral cable in the color yellow has a 3mm push button as well as a 10mm push button. The color scheme allows the cable to be easily recognized at any time and in different lighting conditions.

- 2 MOhm
- 2,4 m
- tested according to BGI 818: 2001

Item no.	WL42084
Model	SG-SK-3/10DK-GE-2400mm-2Mohm
Manufacturer	SAFEGUARD
Manufacturer article no.	SG-SK-3/10DK-GE-2400MM-2MOHM
GPSR manufacturer data	Weidinger GmbH Hertha-Sponer-Str. 1a DE-82216 Gernlinden
Length	2400 mm

Products for the electronic industry



Sales unit	1 piece
Content unit	1 piece
Manufacturer colour information	yellow
Colour	yellow
Incl. battery	no
Connection 1	Push button: Ø 3mm
Connection 2	Push button: Ø 10mm
Electrical resistance	2 MΩ
Connection	3 / 10 mm press stud
ESD certification according to IEC 61340-5-1:2016	yes
ESD compliant	yes
Certified according to BGI818	yes

Other versions

Item no.	Length
WL42084	2400 mm
WL42088	3600 mm