

## ROCIA.focus, RFJ 600/850/S boom luminaire - 10° spotlight

---



Maintenance-free LED technology. Powerful high power LEDs for maximum light. With narrow beam light characteristic. Robust aluminium housing with solid safety glass cover. Viton seal for a high degree of protection. Chemically resistant to many media such as oils or cooling lubricants. Precisely adjustable rod end. Direct connection to machine voltage.

- Direct connection to machine voltage
- without control gear
- Connected loads: 12-28 V; AC and 12-40 V; DC
- Luminous flux: approx. 600 lm
- luminous efficacy: approx. 75lm/W
- Light distribution: direct, narrow beam
- Light colour: neutral white
- Colour rendering (Ra): >80
- Glare control: Optics
- Technology: switchable
- Operation: external

- Lamp cover: Glass screen
- Joint relief: Friction
- Mains connection cable: approx. 3.7 m, with free stranded wire/cable ends
- Mounting: Screw-on flange; base, magnetic base (accessories), wall bracket (accessories)
- Accessories: Ballast
- Special feature: Spot with 10° beam angle
- Em: 5088 lx, Emax: 30053 lx, Emin: 682 lx (measuring distance 50 cm)

<b>item number</b>	<b>WL42262</b>
model	ROCIA.focus
manufacturer	WALDMANN
manufacturer item number	113185000-00668613
length	350 mm
width	200 mm
depth	120 mm
order unit	1 piece
content unit	1 piece
Lamp or magnifier type	Swivel head light
luminous flux	600 lm
connections	12-28 V; AC and 12-40 V; DC
dimnable	no
colour temperature	5000 °K
power	8 W
equipping	LED Energy efficiency class A+
attachment	Pedestal, Table mounting, Wall mounting
housing colour	Aluminium, anodised, black
protection class	3
protection class	67 IP
ESD safe	no