

pole lamp ROCIA.focus, RFD 600/850/D - 40° Flood



Maintenance-free LED technology. Powerful high power LEDs for maximum light. With wide beam light characteristic. Continuous and flicker-free dimming (switchable). Robust aluminium housing with solid safety glass cover. Viton seal for a high degree of protection. Chemically resistant to many media such as oils or cooling lubricants. Precisely adjustable boom. Connection to mains voltage.

- Control gear: Electronic ballast in housing
- Connected loads: 100-240 V; 50/60 Hz
- Luminous flux: approx. 600 lm
- luminous efficacy: approx. 66 lm/W
- Light distribution: direct, wide beam
- Colour rendering (Ra): >80
- Glare control: Optics
- Operation: Pushbutton
- Lamp cover: Glass screen
- Joint relief: Spring

- Mains connection cable: approx. 3 m; mains plug CEE 7/VII
- Mounting: Screw-on flange; base, table clamp (accessories), wall bracket (accessories)
- Special features: Flood with 40° beam angle
- Em: 3255 lx, Emax: 5600 lx, Emin: 1138 lx (measuring distance 50 cm)

Article no.	WL42291
Model	ROCIA.focus RFD600/850/D
Manufacturer	WALDMANN
Manufacturer article no.	113181000-00680167
GPSR manufacturer data	WALDMANN Lichttechnik Peter-Henlein-Straße 5 DE-78056 Villingen-Schwenningen www.waldmann.com
Length	710 mm
Width	300 mm
Depth	105 mm
Sales unit	1 piece
Content unit	1 piece
Lamp or magnifying glass type	rod light
Luminous flux	600 lm
Connection values	100-240 V, 50/60 Hz
Dimmable	yes
Colour temperature	5000 °K
Power	9 W
Equipping	LED Energy efficiency class A+
Fastening	Pedestal, Table mounting, Wall mounting
Case colour	Aluminium, anodised, black
Protection class	1
Protection class	65 IP
ESD compliant	no