

LED-Ringlight RL4-66 NW, natural white, 5.600 K



This LED ring light from Starlight is suitable for everyday use in trade and industry. Thanks to the flexible lighting, it has a large working area which is illuminated very brightly and homogeneously. A robust and easy to fix articulated arm optimizes the perfect working.

- Working distance: 50 mm - 150 mm
- Optimum working distance: approx. 80 mm
- Number of LEDs: 48
- Colour temperature: 5,600 K (natural white)
- LED service life: 50,000 h (L70, manufacturer information)
- brightness control: fine 0 - 100% with memory function
- Power consumption: approx. 7 W
- Power supply input: 100 - 240 V AC, 50/60 Hz
- Power supply unit output: 24 V DC, 1 A
- Operating voltage: 24 V DC
- height: 25,5 mm
- outer diameter: 99 mm
- Inner diameter: 66 mm
- clamping diameter: max. 66 mm
- Internal thread: M67 × 0.75
- Length of supply cable: 0.85 m

- Cable length power supply unit: 1.40 m
- Material: anodised aluminium
- Colour black
- Weight: approx. 230 g
- Control dimensions (L × W × H): 78 mm × 38 mm × 21 mm

Item no.	WL42712
Model	100-010128
Manufacturer	STARLIGHT
Manufacturer article no.	100-010128
GPSR manufacturer data	STARLIGHT Opto-Electronics Flachslander Straße 8 DE-90431 Nürnberg www.starlight-sl.de
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Lamp or magnifying glass type	LED ring light
Colour of light	natural white
Colour temperature	5600 °K
Power	7 W
Case colour	anodised aluminium
ESD compliant	no