

## Electronics diagonal cutter, 200 mm



With cutting edges for soft and medium-hard wire. Without bevel, for flush cutting. Low-friction double spring for smooth and even opening. Push-through precision joint. The polish, in combination with a fine oil film, provides good rust protection - no interference in the circuit due to flaking chrome parts. Cutting edges additionally laser-hardened, cutting edge hardness at least 56 HRC. - Cutting values medium hard wire (diameter): Ø 0,7mm - Cutting values soft wire (diameter): Ø 0,3 / 1,0mm - Jaw length (B): 10mm - Jaw thickness (at joint) (D): 7,5mm - Cutting length mm (C): 17mm - Head width (A): 11mm

- With cutting edges for soft and medium-hard wire
- Without facet, for flush cutting
- Low-friction double spring for smooth and even opening
- Through-holstered precision joint
- The polish in combination with a fine oil film provides good rust protection - no disturbances in the circuit due to flaking chrome parts
- Cutting edges additionally laser-hardened, cutting edge hardness at least 56 HRC

item number	WL42820
model	62 12 120
manufacturer	KNIPEX
manufacturer item number	62 12 120
length	112 mm
width	67 mm
height	17 mm
length with packaging	189 mm

Products for the electronic industry



width with packaging	72 mm
height with packaging	48 mm
Packaging volume	0.637 dm <sup>3</sup>
order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	DIN ISO 9654
RoHS conform	no
VDE	no
ESD safe	no
type of handle	with multi-component sheaths
cutting value wire diameter medium	0.7 mm
cutting value wire diameter soft	1 mm
type of pliers	electronic pliers