

## ESD Stereomicroscope A60 S, binocular, 30x

---



LED ring light: 16 Med Power SMT LEDs

The Leica A60 S stereomicroscope system with swivel arm stand is configured for all industrial inspection, assembly and quality control applications. Simplify your inspection and rework of printed circuit boards (PCB) in the electronics industry. The Leica A60 S optimizes productivity and quality in the manufacture of medical devices (hearing aids, pacemakers, catheters, etc.). With the Leica A60 S you experience 100% more depth of field than with conventional stereomicroscopes. The energy-saving LED lighting makes lamp changes unnecessary, reduces operating costs and is easy on your eyes. 100% more depth of field with Leica FusionOptics™ technology - Easier handling, less refocusing, große time saving

More space to work with 122 mm working distance - Best access to the workpiece and easier handling with tools. The LED ring light with removable diffuser - bright, even and colour-neutral. Pleasant working due to lower reflections on shiny workpieces. Large 46 mm object field - ideal for manufacturing and inspection tasks. Stable leg arm stand for large, recurring samples.

- Magnification 5 to 30x With FusionOptics technology
- With the Leica A60 you experience 100% more depth of field than with conventional

## stereomicroscopes

- Eyepieces: 10x/23 B, adjustable, suitable for spectacle wearers
- Interpupillary distance: 52 - 76 mm
- Tripod: Max. Throat: 560 mm
- Dimensions of the base: 230 x 266 mm
- Earthing point: Ø 4.2 mm
- Quick amortisation through LED lighting
- 10 brightness levels
- LED service life: 50000 h
- Max. Throat: 560 mm
- Earthing point: 4.2 mm
- Dimensions T-clamp: 105 x 100 mm
- Max. Throat: 995 mm
- Length up to 100 mm Table thickness

item number	WL43031
model	LEICA A60 S
manufacturer	LEICA
order unit	1 piece
content unit	1 piece
voltage	100 – 240 V
lenticular	binocular
(Optimal) working distance	122 mm
Product type	stereomicroscope
Viewing angle	38 °
Version tripod	Swivel arm stand
camera zoom	30x
colour temperature	5600 °K
power	15 W
magnification	6:1
equipping	LED ring light: 16 Med Power SMT LEDs
ESD safe	yes