

ESD screwdriver TORX T2



- ESD screwdriver
 - slim, ergonomically shaped handle made of conductive plastic
 - The rotating centering head guarantees precise and fatigue-free working
 - Blade: high-quality chrome-vanadium-molybdenum steel, hardened throughout, matt chrome-plated
 - Handle: black precision handle with yellow rotating cap
- metric thread: M 1,0-1,2

item number	WL43327
model	6-657
manufacturer	BERNSTEIN
manufacturer item number	6-657
width	85 mm

Products for the electronic industry



length with packaging	180 mm
width with packaging	85 mm
height with packaging	17 mm
order unit	1 piece
content unit	1 piece
ESD-standard	All ESD tools comply with the ESD standard IEC 61340-5-1. The leakage resistance of the BERNSTEIN ESD tools is in the range of the ideal value between 106 and 109 Ohm.
VDE	no
type of screw	T2
ESD safe	yes
packaging mass	piece
type of screwdriver	normal screwdrivers
tool length	120 mm
screwdriver size	mm: T2
handle length	80 mm
blade diameter	2.5 mm
blade length	40 mm

Other versions

item number	type of screw
WL43233	PH000
WL43234	PH00
WL43235	PH0
WL59997	PH1
WL43324	T1
WL43327	T2
WL43328	T3
WL43329	T4
WL43332	T5
WL43333	T6
WL59996	T7
WL59995	T8

WL59994	T9
WL59993	T10
WL43222	1,5 mm
WL43224	2 mm
WL43225	2,5 mm
WL43226	3 mm
WL59999	3,5 mm
WL59998	4 mm