

## Cable shears with double cutting edge, with anti-trap protection, plastic-coated handles, Ø 20 mm / 70 mm<sup>2</sup>, 200 mm



For cutting Cu and Al cables. Not suitable for steel wire and hard-drawn copper conductors. Hardened cutting edges with precision grinding. Cuts smoothly and cleanly without crushing. By dividing the cutting process into pre-cut (insulating jacket in the front cutting area) and post-cut (conductor in the rear cutting area), cables up to Ø 20 mm can be cut in one-hand operation. Low power requirement due to favourable transmission ratios and special cutting geometry. Pinch protection prevents crushing injuries. Adjustable screw joint, self-locking. - Cutting value Cu-cable, stranded: 70mm<sup>2</sup> - Cutting value Cu-cable, stranded: Ø 20mm - AWG: 2 / 0

- For cutting Cu and Al cables
- Not suitable for steel wire and hard drawn copper conductors
- Hardened cutting edges with precision grinding
- Cuts smoothly and cleanly without crushing
- By dividing the cutting process into pre-cut (insulating sheath in the front cutting area) and post-cut (conductor in the rear cutting area), cables up to Ø 20 mm can be cut in one-hand operation
- Low power requirement due to favourable transmission ratios and special cutting geometry
- Pinch protection prevents crushing injuries
- Adjustable screw joint, self-locking

Item no.	WL43372
Model	95 11 200
Manufacturer	KNIPEX
Manufacturer article no.	95 11 200
GPSR manufacturer data	KNIPEX-Werk

Oberkamper Strasse 13  
 DE-42349 Wuppertal-Cronenberg  
 www.knipex.de

Length	200 mm
Width	21 mm
Height	15 mm
Length with packaging	236 mm
Width with packaging	88 mm
Height with packaging	52 mm
Volume with packaging	1.08 dm <sup>3</sup>
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
RoHS compliant	no
Surface	burnished
VDE	no
ESD compliant	no
Tool length	200 mm
AWG	2 / 0
Grip (expression)	Covered with plastic
Scissor type	cable shears
Cutting value copper cable, stranded	70 mm <sup>2</sup>
Cutting value copper cable, stranded (diameter)	20 mm