

System luminaire TAMETO - SAHQ 88 R, mounting top/fixed, dimmable, 5000 K



The Tameto system luminaire from Waldmann is convincing on many levels: Maintenance-free LED technology, extremely homogeneous, glare-free and flicker-free light as well as light emission with a cone prism structure for perfect glare control. The Tameto system luminaire is available in various lengths for different desk widths and lighting requirements to equip the perfect industrial workplace. The robust aluminium housing and enclosed design protect the inside of the system luminaire and work surface from contamination.

- Control gear: Electronic ballast
- Connected loads: 220-240 V, 50/60 Hz
- Luminous flux: 2900 lm
- Luminaire light yield: approx. 87 lm/W
- Light colour: neutral white
- Colour rendering (Ra): >80
- glare control: conical prismatic diaphragm
- Technique: infinitely dimmable
- Operation: Rocker switch
- Mains connection cable: approx. 3 m; mains plug CEE 7/VII
- Mounting: screw-on tab
- Length: 1256 mm
- Em: 1071 lx, Emax: 1448 lx, Emin: 659 lx (measuring distance 100 cm)

| | |
|--------------------------|--------------------|
| item number | WL44144 |
| model | SAHQ 88 R |
| manufacturer | WALDMANN |
| manufacturer item number | 112980000-00687095 |
| length | 1300 mm |

| | |
|------------------------|---|
| width | 220 mm |
| depth | 120 mm |
| order unit | 1 piece |
| content unit | 1 piece |
| Lamp or magnifier type | workplace light |
| luminous flux | 2900 lm |
| connections | 220-240 V; 50/60 Hz |
| colour temperature | 5000 °K |
| power | 33 W |
| equipping | LED, energy efficiency class A+ |
| attachment | Ceiling mounting |
| housing colour | Aluminium/plastic, anodised, aluminium coloured (colourless anodised) |
| protection class | 1 |
| protection class | 20 IP |
| ESD safe | no |