Screwdriver set, 21 pieces Kraftform Compact Micro-Set ESD/21



Kraftform Compact Micro-Set for precision mechanical applications. Suitable for bits with 4 mm half-moon drive (Wera Series 9) and bits with 4 mm HIOS drive (Wera Series 21). Electrical surface resistance < 10 to the power of 9 Ohm for reliable protection against electrostatic energy. Manufactured according to DIN EN 61340-5-1. Compact handle/interchangeable blade system for lightning-fast blade replacement. Kraftform Micro Handle with rotating cap and fast rotation zone for lightning-fast twirling, no more time-consuming re-gripping necessary. Kraft zone with integrated soft zones for the transmission of high release and tightening torques. Precision zone directly above the blade for the correct rotation angle for adjustment work. Bits for hand- and machine-operated screw connections. Lightning-fast bit fixing: simply push the bit into the receptacle, automatic locking, secure fit. To change the bit, simply push the sleeve forward and remove the bit. Free-running actuating sleeve for easy guidance of the tool during the screwing process.

- Electrostatic safe tool due to surface resistance of < 10^9 Ohm
- Kraftform Micro ESD bits hand holder
- Hand-held holder with roll-off protection, rotating cap and quick-change chuck
- Bit holder suitable for holding bits with 4 mm half-moon or HIOS drive
- In practical folding case

Item no.	**WL44881**
Model	Kraftform Kompakt Micro 21 ESD 1
Manufacturer	WERA
Manufacturer article no.	05135973001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	155 mm
Width	100 mm
Height	35 mm
Length with packaging	155 mm
Width with packaging	100 mm
Height with packaging	35 mm
Scope of delivery	1013 Force form Micro ESD - 1 x 97 mm 867/9 C TORX®: - 1 x TX 1 x 44 mm - 1 x TX 2 x 44 mm - 1 x TX 3 x 44 mm - 1 x TX 4 x 44 mm - 1 x TX 5 x 44 mm 867/9 IPR TORX® PLUS: - 1 x 1 IPR x 44 mm 800/9 C - 1 x 0.23 x 1.5 x 44 mm - 1 x 0.35 x 2.5 x 44 mm 851/9 C: - 1 x PH 000 x 44 mm - 1 x PH 00 x 44 mm - 1 x PH 0 x 44 mm 867/9 C TORX PLUS®: - 1 x 1 IP x 44 mm - 1 x 2 IP x 44 mm - 1 x 3 IP x 44 mm - 1 x 4 IP x 44 mm 872/9: - 1 x m x 44 mm

	- 1 x 00 x 44 mm - 1 x F x 44 mm - 1 x 0 x 44 mm 869/9: - 1 x 2.5 x 44 mm
Sales unit	1 set
Content unit	1 set
VDE	no
ESD compliant	yes
Number of parts in the tool set	21-piece