

## Automatic soldering unit for difficult soldering applications



### Description

- for difficult soldering applications with high heat requirements
- selective solution with automatic soldering tip change
- the TRA470 automatic soldering iron in combination with the CS2R470 soldering tip stand allows automatic soldering tip change as soon as the tip is worn out
- Solder wire feeder SFR is mounted on the TRA soldering head
- Tip cleaner CLMR with 50 mm diameter cleans the soldering tip in one second and thus increases the heat transfer performance
- suitable lance series: R470
- R470 tips and GSFR Tube Set are not included

### Product details

item number	<b>WL44898</b>
manufacturer	JBC
manufacturer item number	HA470A-5B
model	HA470A-5A
dimensions with packaging (LxWxH)	545 mm x 345 mm x 275 mm
scope of supply	1 UCR470-5A Control unit for R470 1 CS2R470-B soldering tip holder for R470

Products for the electronic industry



	1 TRA470-B Automatic soldering iron for R470 1 SFR-B solder wire feed 1 CLMR-A soldering tip cleaner
order unit	piece
nominal power	250 W
voltage	42 V
temperature range °C	90–450 °C
Tip to ground resistance	< 2 Ohm
ambient operating temperature	10–40 °C
wire diameter	0.5–1.5 mm