

Automatic soldering unit for difficult soldering applications



Please note: R470 tips and GSFR tube set are not included

- for difficult soldering applications with high heat requirements
- selective solution with automatic soldering tip change
- the TRA470 automatic soldering iron in combination with the CS2R470 soldering tip stand allows automatic soldering tip change as soon as the tip is worn out
- Solder wire feeder SFR is mounted on the TRA soldering head
- Tip cleaner CLMR with 50 mm diameter cleans the soldering tip in one second and thus increases the heat transfer performance
- suitable for series: R470
- R470 tips and GSFR Tube Set are not included

item number	WL44898
model	HA470A-5B
manufacturer	JBC
manufacturer item number	HA470A-5B
length with packaging	545 mm

width with packaging	345 mm
height with packaging	275 mm
scope of supply	1 UCR470-5A Control unit for R470 1 CS2R470-A soldering tip holder for R470 1 TRA470-B Automatic soldering iron for R470 1 SFR-B solder wire feed 1 CLMR-A soldering tip cleaner
order unit	1 piece
content unit	1 piece
nominal power	250 W
voltage	42 V
temperature range °C	90 – 450 °C
Tip to ground resistance	< 2 Ohm
ambient operating temperature	10 – 40 °C
wire diameter	0.5 – 1.5 mm