

interchangeable blade Pozidriv, PZ1 x 175 mm, 3.8 Nm



- Meets your requirements: Variable adjustable torque covers a wide range of applications
- Reduces your costs: Electrostatically dissipative tools protect electronic components from destruction
- Protects your health: with patented SoftFinish® handle design for hand and muscle-friendly work
- Increases your efficiency: the right torque protects you from material damage and reworking
- Standards: IEC 61340-5-1
- DIN EN ISO 6789
- Application For controlled bolting to electrostatically sensitive components at a specified torque, in combination with a Wiha Torque 4 mm ESD interchangeable blade.

Item no.	WL45024
Model	28592
Alternative article name	285921
Manufacturer	WIHA
Manufacturer article no.	26148
GPSR manufacturer data	Wiha Werkzeuge GmbH Obertalstraße 3-7 DE-78136 Schonach www.wiha.com
Length with packaging	194 mm
Width with packaging	35 mm
Height with packaging	24 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Standards	Blade tip DIN ISO 8764-1.
Product series	28592
Torque blade length	175 mm
Torque blade working length	42 mm

Products for the electronic industry



Hexagon blade diameter	4 mm
Pozidriv	PZ1
VDE	no
Screw type	PZ1
ESD compliant	no
Packaging dimensions	piece
Screwdriver type	torque screwdriver
Torque (max.)	3.8 Nm
Tool length	175 mm

Other versions

Item no.	Screw type
WL45026	PH00
WL45028	PH1
WL45024	PZ1
WL45102	inner square

