ESD earthing tile, T-Lock, light gray, 500 x 500 x 7 mm, 1 piece



- with grounding point (1 piece)
- certified according to ISO90001
- ISO 61340/5
- EN 1081, EN 1815 & EN6356
- Surface resistance of the tiles is between 3.0 x 10^4 Ohm/m2 and 3 x 10^6 Ohm
- Resistance to ground is between 3.6 x 10^5 Ohm and 9.5 x10^5 Ohm
- fire-retardant - class Bfl s1
- anti-slip
- chemical resistant
- reduces dust and noise
- easy installation thanks to interlocking joints - click-and-use installation
- Insulation of the floor against cold and moisture

Item no.	**WL45262**
Model	ECOTILE-16.104 HG
Manufacturer	ECOTILE
Manufacturer article no.	16.104
GPSR manufacturer data	ecotile Flooring Sedgwick Road Unit 15

	GB-LU4 9DT Luton www.ecotileflooring.com
Length	500 mm
Width	500 mm
Height	7 mm
Sales unit	1 piece
Content unit	1 piece
Manufacturer colour information	light gray (RAL 7004)
Colour	light grey
Connection system	T-Lock
Typical surface resistance (Rpp)	zwischen 3,0 x 10^4 Ohm/m2 und 3 x 10^6 Ohm
Surface texture	flat
Strength	7 mm
Type of surface	floor tile
ESD compliant	yes

Other versions

Item no.	Strength
WL45262	**7 mm**