

## DT3 data terminal + display, RFID reader and relay contact



### Description

The DATA Terminal DT3 logs the measurement data of the Personnel Grounding Tester PGT®120.COM. In addition, this version includes an RFID reader, a display and a switching contact.

- Can be variably integrated into existing infrastructure
- Several PGT®120.COM stations can be combined to form a network
- Existing operating passes or time recording cards can still be used
- Customer systems can be connected via open database interface
- Measurement data available for further processing in a few seconds
- Different databases can be used
- Combination with existing access systems is possible
- Secure, encrypted network communication
- Interfaces: 4 x USB, 1 x D-SUB9 for PGT120.COM, 1 x RJ45 - LAN, 1 x RJ12 - Relay, 1 x Micro, USB - RFID Reader, 1 x Micro USB - POWER 5VDC
- Dimensions: 120 x 150 x 63 mm
- Weight: 350 g
- Output: Semiconductor relay 24 VDC (16V/AC)/ 2A - Resistive load Protective circuit required for inductive load)
- Internal RFID Reader: Legic

### Product details

Products for the electronic industry



item number	WL45330
manufacturer	WARMBIER
manufacturer item number	7100.PGT120.COM.DT3
model	7100.PGT120.COM.DT3
dimensions (LxWxH)	120 mm x 150 mm x 63 mm
scope of supply	1 x DATA terminal DT3 1 x power supply 100-240 VAC/5 VDC with interchangeable adapter (EU/USA) 1 x USB to Micro-USB connection cable (for activation of the internal RFID card reader) 1 x short instruction (German / English)
order unit	piece
interfaces	USB