

2 channel control unit, 230 V



- manages 2 tools simultaneously
- Compatible with 10 handpieces: PA120-A, AM120-A, T210-A, T210-NA, T245-A, T245-NA, HT420-A, DS360-A, DR560-A, AP250-A
- has the Dynamic Soldering Profiles function: temperature fluctuations when soldering ceramic chip components such as MLCC are avoided
- up to 25 fully configurable solder profiles can be stored
- Sleep and rest mode of the soldering tips
- adjustable max. and min. temperature adjustable for the user
- 3 temperature levels adjustable - for solder joints with different heat requirements
- Soldering Graphics: Real-time visualization of peak temperature and power delivered to the solder joint during the soldering process
- 10 different languages available: English, German, Spanish, French, Italian, Portuguese, Russian, Japanese, Korean and Chinese
- Peak power: 150 watts per tool

item number	WL45354
model	DDE-2C
manufacturer	JBC
manufacturer item number	DDE-2C
length	148 mm
width	120 mm
height	232 mm
scope of supply	1 DDE-2C control unit
order unit	1 piece
content unit	1 piece
heat-up rating	150 W
voltage (to)	23 V
temperature range °C	90 – 450 °C
ambient operating temperature	10 – 40 °C
connections	USB-B (rear), USB-A (front), Robot RS-232, Equipotential bonding
number of channels	2